Beaverton School District BSD ADMIN OFFICE TENANT IMPROVEMENT

1260 NW WATERHOUSE AVE BEAVERTON, OR 97006

CONTENT

Improvements will include adding two ADA accessible restrooms, updated casework and sink fixture, and a new door into the east office suite on the first floor. The second floor will have two new doors added to the Team Room.



ARCHITECTURAL ABBREVIATIONS

&	AND	EJ	EXPANSION JOINT	L	LENGTH
AB	ANCHOR BOLT	EL	ELEVATION	LAV	LAVATORY
ACT	ACOUSTICAL CEILING TILE	ELEC	ELECTRICAL	LB	LAG BOLT
ADD	ADDENDUM	ENGR	ENGINEER	LKR	LOCKER
AESS	ARCHITECTURAL EXPOSED STRUCTURAL STEEL	EOS	EDGE OF SLAB	LS	LANDSCAPING
AFF	ABOVE FINISH FLOOR	EQ	EQUAL	LVR	LOUVER
ALS	AREA LIGHT STANDARD	EQUIP	EQUIPMENT	MATL	MATERIAL
ALUM	ALUMINUM	ES	EACH SIDE	MAX	MAXIMUM
ANOD	ANODIZED	EW	EACH WAY	MB	MARKERBOARD
BD	BOARD	EXP	EXPANSION	MECH	MECHANICAL
BLDG	BUILDING	EXT	EXTERIOR	MED	MEDIUM
BLKG	BLOCKING	FA	FIRE ALARM	MEZZ	MEZZANINE
BM	BENCH MARK	FD	FLOOR DRAIN	MFR	MANUFACTURER
BOT	BOTTOM	FDN	FOUNDATION	MIN	MINIMUM
BTWN	BETWEEN	FE	FIRE EXTINGUISHER	MIR	MIRROR
С	CHANNEL	FEC	FIRE EXTINGUISHER CABINET	MISC	MISCELLANEOUS
СВ	CATCH BASIN	FECB	FIRE EXTINGUISHER CABINET WITH BLANKET	MTD	MOUNTED
CCTV	CLOSED CIRCUIT TELEVISION	FF	FINISH FLOOR	MTL	METAL
CG	CORNER GUARD	FIN	FINISH	N	NEW
CIP	CAST IN PLACE CONCRETE	FL	FLOOR	NA	NOT APPLICABLE
CJ	CONTROL JOINT	FO	FACE OF	NIC	NOT IN CONTRACT
CL	CENTERLINE	FOC	FACE OF CONCRETE	NOM	NOMINAL
CLG	CEILING	FOF	FACE OF FINISH	NTS	NOT TO SCALE
CLR	CLEAR	FOM	FACE OF MASONRY	OA	OVERALL
CMU	CONCRETE MASONRY UNIT	FOS	FACE OF STUD	OC	ON CENTER
CONT	CONTINUOUS	FRT	FIRE RETARDANT TREATED	OD	OVERFLOW DRAIN
CORR	CORRIDOR	FTG	FOOTING	OFCI	OWNER FURNISHED CONTRACTOR
CR	CLASSROOM	FURR	FURRING	OFOI	OWNER FURNISHED OWNER INSTA
CSJ	CONSTRUCTION JOINT	GA	GAUGE	ОН	OVERHEAD
CSMT	CASEMENT	GALV	GALVANIZED	OPNG	OPENING
СТ	CERAMIC TILE	GB	GRAB BAR	OPP	OPPOSITE
CTR	CENTER	GC	GENERAL CONTRACTOR	OS	OUTSIDE
DBL	DOUBLE	GL	GLASS	PL	PROPERTY LINE
DF	DRINKING FOUNTAIN	GND	GROUND	PLAS	PLASTER
DIAG	DIAGONAL	GVP	GYPSUM VENEER PLASTER	PLYWD	PLYWOOD
DIM	DIMENSION	GWB	GYPSUM WALL BOARD	PSF	PER SQUARE FOOT
DISP	DISPENSER	HB	HOSE BIBB	PT	PRESSURE TREATED
DN	DOWN	HC	HANDICAP	PVMT	PAVEMENT
DP	DAMPROOFING	HM	HOLLOW METAL	R	RADIUS
DR	DOOR	HPC	HIGH PERFORMANCE COATING	RCP	REFLECTED CEILING PLAN
DS	DOWNSPOUT	HVAC	HEATING, VENTILATION, AND AIR CONDITIONING	RD	ROOF DRAIN
DTL	DETAIL	HW	HOT WATER	RDO	ROOF DRAIN WITH OVERFLOW DR
DWG	DRAWING	INSUL	INSULATION	REF	REFERENCE
E	EXISTING	INT	INTERIOR	REFR	REFRIGERATOR
EA	EACH	JAN	JANITOR	REQ'D	REQUIRED
EF	EXHAUST FAN	JST	JOIST	REV	REVISE OR REVISION
		JT	JOINT	RM	ROOM

Bid Set

DEFERRED SUBMITTALS

07 84 00 FIRESTOPPING 13 48 53 SEISMIC ANCHORAGE

	RO	ROUGH OPENING
	SAHTS	SELF-ADHERED HIGH TEMPERATURE SHEET
	SAM	SELF-ADHERED MEMBRANE
	SC	SOLID CORE
	SECT	SECTION
	SF	SQUARE FOOT
	SG	PREFINISHED SHEET METAL GUTTER
	SHT	SHEET
	SHTG	SHEATHING
	SHWR	SHOWER
	SIM	SIMILAR
	SJ	SEISMIC JOINT
	SM	SHEET METAL
	SP	SPLASH PAN
	SQ	SQUARE
	SS	STAINLESS STEEL
	STD	STANDARD
	STL	STEEL
	STOR	
	SUSP	STRUCTURAL SUSPENDED
	303P T	TEMPERED GLAZING
	T&G	TONGUE AND GROOVE
	T/M	TO MATCH
	TC	TOP OF CURB
	TEL	TELEPHONE
OR INSTALLED	THK	THICK
TALLED	TJ	TOOL JOINT
	то	TOP OF
	TOD	TOP OF DECK
	TOS	TOP OF STRUCTURE
	TP	TOILET PAPER
	TS	TUBE STEEL
	TYP	TYPICAL
	UNFIN	UNFINISHED
	UNO	UNLESS NOTED OTHERWISE
	VB	VAPOR BARRIER
	VERT	VERTICAL
	VEST	VESTIBULE
	VFY	VERIFY
	W/	WITH
RAIN	W/O	WITHOUT
	WC	WATER CLOSET
	WD	WOOD
	WF	WIDE FLANGE
	WH	WATER HEATER
	WP	
	WRB	WATER-RESISTIVE BARRIER

WΤ

WEIGHT


SHEET INDEX

General G0000	COVER PAGE
G1112	WALL TYPES - INTERIOR
G1113	HORIZONTAL ASSEMBLIES INTERIOR
G1201	FIRE, LIFE, & SAFETY PLANS
Architecture	
AD1201	ARCHITECTURAL DEMOLITION PLANS
A1101	FLOOR PLAN - GROUND LEVEL
A1102	FLOOR PLAN - LEVEL 02
A2101	BUILDING ELEVATIONS
A4101	ENLARGED PLANS - RESTROOMS
A4102	ENLARGED PLANS - BOARDROOM DAIS
A6101	DOOR & RELITE SCHEDULE & TYPES
A6102	SIGNAGE, CASEWORK SCHEDULE & TYPES
Plumbing	
P0001	SYMBOL LIST AND GENERAL NOTES - PLUMBING
P0002	SCHEDULES - PLUMBING
P1400	FLOOR PLAN - UNDERGROUND - PLUMBING
P1401	FLOOR PLAN - GROUND LEVEL - PLUMBING
Mechanical	
M0001	SYMBOL LIST, GENERAL NOTES, DETAILS, & SCHEDULES - MECHANICAL
M1401	FLOOR PLAN - GROUND LEVEL - MECHANICAL
Electrical	
E0001	SYMBOL LIST AND GENERAL NOTES - ELECTRICAL
E1201	DEMOLITION PLANS - ELECTRICAL
E1401	FLOOR PLAN - GROUND LEVEL - ELECTRICAL
E1501	REFLECTED CEILING PLAN - GROUND LELVEL - LIGHTING
E1502	REFLECTED CEILING PLAN - LEVEL 02 - LIGHTING
E6001	SCHEDULES - ELECTRICAL


ARCHITECTURAL SYMBOLS

Room & Unit Tags Room Name 10101	Door & Relite Tag
Wall Tags	101 <u>Window Tag</u>
Floor Tags	Keynote Tag
Roof Tags	Casework Tag
<u>Ceiling Tags</u>	Equipment Tag
Finish Tags	Revision Tags
Floor Finish Room Tags ROOM NAME A101 FINISH BASE	North Arrow

<u>Titlemark</u>
1 Vie SCALE
Building Section N




Building Exterior Elevation Marker



Detail Section


<u>Grid</u>

True North Project North





CLIENT **Beaverton School** District BEAVERTON SCHOOL DISTRICT 1260 NW WATERHOUSE AVENUE, BEAVERTON, **OREGON 97006** ARCHITECTURE Arcadis Architects (USA) Inc. 830 NE Holladay Street Portland, OR 97232 NAME: Jim Fitzpatrick EMAIL: jim.fitzpatrick@IBIGroup.com M.E.P. Interface Engineering, Inc. 100 SW Main St. #1600 Portland, OR 97204 NAME: Mark O'Leary EMAIL: marko@interfaceeng.com ISSUES DESCRIPTION BID SET DATE 2023-04-2 ARCADIS PROJECT **BSD ADMIN OFFICE** TENANT IMPROVEMENT PROJECT NO: 142595 DATE: 2023-03-31 Bid Set SHEET NUMBER G0000


FURRING STRIPS AT THINNER WALL SSEMBLY AS NEEDEDIntersection of two wall types with different continous gypsum board clinish face - see interior clevationsAlgo studs controus ULL LENGTH of wall ULL type ULL type ULL type ULL type ULL type ULL type ULL type ULL typeFOR ALL CASES WHEN TWO WALLS OF DIFFERENT WIDTHS MEET IN AN EXPOSED LOCATION. ENSURE FINISH Ace is flush.	 NOTED WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMA ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT IN TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED O SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPL FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DF BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS (ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLIC/ ASSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND FROM STRU FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPEC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS RE CODE. AT RATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENT SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORI INDICATING "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENI 9. PROVIDE FIRE BLOCKING IN CONCEALED SPACES OF STUD WALLS PARTITIONS VERTICALLY AT THE CEILING AND FLOOR LEVELS AND HORIZONTALLY AT INTERVALS NOT EXCEEDING 10 FEET. WHERE LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR V WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS OTHERV NOTED.
WALL TYPES TRANSITION SCALE: 1 1/2" = 1'-0"	























HORIZONTAL ASSEMBLY NOT NOTED HORIZONTAL ASSEMBLY TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATION.

AND SOFFIT.

- 2. SEE FLOOR FINISH PLAN FOR LOCATION AND EXTENT OF FLOOR FINISHES.

Γ	E	S	•

3. SEE REFLECTED CEILING PLANS FOR LOCATION AND EXTENT OF CEILING






	TABLE	1004.1.2	2 OCCL	JPANT L	OAD
		OCCUPANCY	LOAD	OCCUPANT	
NAME	SIZE	TYPE	FACTOR	LOAD	LEVEL
ONFERENCE	293 SF	B (303.1.2)	15	19.5	FINISHED FLOOR
OMPERENCE	293 SF 3160 SF	A-3	15	210.7	FINISHED FLOOR
					FINISHED FLOOR
	19826 SF	B	150	132.2	
OSET	39 SF	B	300	0.1	FINISHED FLOOR
	600 SF	B (303.1.2)	30	40	FINISHED FLOOR
NISHED FLOOR	23918 SF			402.5	
DNFERENCE	372 SF	B (303.1.2)	15	24.8	FINISHED FLOOR 2
OLLABORATION	953 SF	A-3 (ACC)	15	65.3	FINISHED FLOOR 2
ISINESS AREAS	20088 SF	В	150	134	FINISHED FLOOR 2
AINING	588 SF	B (303.1.2)	15	39.2	FINISHED FLOOR 2
NFERENCE	371 SF	B (303.1.2)	15	24.7	FINISHED FLOOR 2
NFERENCE	294 SF	B (303.1.2)	15	19.6	FINISHED FLOOR 2
NFERENCE	419 SF	B (303.1.2)	15	27.9	FINISHED FLOOR 2
AK	461 SF	B (303.1.2)	15	30.7	FINISHED FLOOR 2
SHED FLOOR 2	23546 SF			366.2	
DNFERENCE	743 SF	B (303.1.2)	15	49.5	FINISHED FLOOR 3
NFERENCE	147 SF	B (303.1.2)	15	4.9	FINISHED FLOOR 3
LLABORATION	715 SF	B (303.1.2)	15	47.7	FINISHED FLOOR 3
NFERENCE	288 SF	B (303.1.2)	15	19.2	FINISHED FLOOR 3
LLABORATION	335 SF	B (303.1.2)	15	22.3	FINISHED FLOOR 3
NFERENCE	147 SF	B (303.1.2)	15	9.8	FINISHED FLOOR 3
_AB	584 SF	В	50	11.7	FINISHED FLOOR 3
EN OFFICE	19983 SF	В	150	133.3	FINISHED FLOOR 3
LLABORATION	194 SF	B (303.1.2)	15	12.9	FINISHED FLOOR 3
LLABORATION	420 SF	B (303.1.2)	15	28	FINISHED FLOOR 3
NFERENCE	423 SF	B (303.1.2)	15	28.2	FINISHED FLOOR 3
NISHED FLOOR 3	23980 SF			367.5	-
	71443 SF			1136.2	

OFFSETTING TIMES.	IF THE DISTRICT'S CENTRAL OFFICE DURING R E COMMUNITY ROOM (A-ASSEMBLY) USED AFT
RESTROOMS ON THE GRO SPACE DURING OCCUPIED	UND FLOOR WILL BE MADE AVAILABLE TO THE HOURS.
BUSINESS FIXTURE COUN	T - (REGULAR BUSINESS HOURS)
TOTAL OCCUPANT LOAD:	925.5 PEOPLE (462.5 EACH GENDER)
	861 PEOPLE (B - BUSINESS) 64 PEOPLE (A - ASSEMBLY)
WATER CLOSETS:	10 REQUIRED FOR MEN // 9 WC + 6 URINALS 11 REQUIRED FOR WOMEN // 12 PROVIDED
	9.6 (B @ 460.5 PER GENDER - 1:25 FOR FIRST .26 MEN (A @ 33 PER GENDER - 1:125) .51 WOMEN (A @ 33 PER GENDER - 1:65)
LAVATORIES:	7 REQUIRED PER GENDER//16 TOTAL PROVI
	6.3 (B @ 460.5 PER GENDER - 1:40 FOR FIRST 0.5 (A @ 33 PER GENDER - 1:200)
DRINKING FOUNTAINS:	NOT REQUIRED FOR B-OCCUPANCY, 1 REQU FOR ASSEMBLY.
	NOTE: WATER IS PROVIDED WITHIN EACH BH EMPLOYEES ON EACH LEVEL
ASSEMBLY FIXTURE COUN	IT - (AFTER WORK HOURS)
	IT - (AFTER WORK HOURS) 212 PEOPLE (106.0 EACH GENDER)
TOTAL OCCUPANT LOAD:	212 PEOPLE (106.0 EACH GENDER)
	212 PEOPLE (106.0 EACH GENDER) 212 PEOPLE (A-3 - AUDITORIUM; NO FIXED SE 1 REQUIRED FOR MEN // 2 WC + 2 URINALS P
TOTAL OCCUPANT LOAD:	212 PEOPLE (106.0 EACH GENDER) 212 PEOPLE (A-3 - AUDITORIUM; NO FIXED SE 1 REQUIRED FOR MEN // 2 WC + 2 URINALS P 2 REQUIRED FOR WOMEN // 3 PROVIDED 0.85 (A-3 @ 106 MEN - 1:125)
TOTAL OCCUPANT LOAD:	212 PEOPLE (106.0 EACH GENDER) 212 PEOPLE (A-3 - AUDITORIUM; NO FIXED SE 1 REQUIRED FOR MEN // 2 WC + 2 URINALS P 2 REQUIRED FOR WOMEN // 3 PROVIDED 0.85 (A-3 @ 106 MEN - 1:125) 1.63 (A-3 @ 106 MOMEN - 1:65) NOTE: A FAMILY RESTROOM IS NOT REQUIRE THE ASSEMBLY OCCUPANCY REQUIRES LESS
TOTAL OCCUPANT LOAD: WATER CLOSETS:	212 PEOPLE (106.0 EACH GENDER) 212 PEOPLE (A-3 - AUDITORIUM; NO FIXED SE 1 REQUIRED FOR MEN // 2 WC + 2 URINALS P 2 REQUIRED FOR WOMEN // 3 PROVIDED 0.85 (A-3 @ 106 MEN - 1:125) 1.63 (A-3 @ 106 WOMEN - 1:65) NOTE: A FAMILY RESTROOM IS NOT REQUIRE THE ASSEMBLY OCCUPANCY REQUIRES LESS CLOSETS
TOTAL OCCUPANT LOAD: WATER CLOSETS:	212 PEOPLE (106.0 EACH GENDER) 212 PEOPLE (A-3 - AUDITORIUM; NO FIXED SE 1 REQUIRED FOR MEN // 2 WC + 2 URINALS P 2 REQUIRED FOR WOMEN // 3 PROVIDED 0.85 (A-3 @ 106 MEN - 1:125) 1.63 (A-3 @ 106 WOMEN - 1:65) NOTE: A FAMILY RESTROOM IS NOT REQUIR THE ASSEMBLY OCCUPANCY REQUIRES LESS CLOSETS 1 REQUIRED PER GENDER//4 TOTAL PROVID

FIRE LIFE SAFETY (BY GENERAL

CHERNER AND FIRE LIFE SAFETY REQUIREMENTS TO BE COMPLETED BY THE GENERAL CONTRACTOR. PROVIDE THE APPROPRIATE SUBMITTAL TO THE ARCHITECT FOR REVIEW AND COORDINATION PRIOR TO SUBMITTING TO THE AUTHOROITY HAVING JURISDICTION.

CODE REQUIRED SIGANGE

- A. PROVIDE REQUIRED CODE REQUIRED SIGNAGE AS PRESCRIBED BY THE OREGON STRUCTURAL SPECIALTY CODE AND THE INTERNATIONAL FIRE CODE. COORDINATE LOCATION WITH ARCHITECT AND AUTHORITY HAVING JURISDICTION PRIOR TO
- B. THE FOLLOWING ITEMS ARE TYPICALLY PROVIDED BY THE GENERAL CONTRACTOR, BUT MAY NOT EXHAUSTIVE OF ALL UNIQUE PROJECT REQUIREMENTS. COORDINATE EXTENT OF CODE REQUIRED SIGNAGE WITHIN THIS PROJECT WITH ARCHITECT OF RECORD PRIOR
- C. OREGON SPECIALTY STRUCTURAL CODE BASED ON THE INTERNATIONAL BUILDING
 - TWO-WAY COMMUNICATION DEVICES (IBC 1007.8.2) - AREAS OF REFUGE (IBC 1007.9) - DELAYED EMERGENCY EXIT DOORS (IBC 1008.1.9) - KEY LOCKS ON EGRESS SIDE OF DOORS (IBC 1008.1.9)
- ACCESSIBILITY ELEMENTS AND DIRECTIONAL SIGNAGE (IBC 1110) - ELEVATOR EMERGENCY SIGNS (IBC 3002.3) D. OREGON FIRE CODE - BASED ON THE INTERNATIONAL FIRE CODE (IFC)
 - PREMISES IDENTIFICATION (IFC 505.1) - FIRE PROTECTION EQUIPMENT SIGNS (IFC 509.1) - ELECTRICAL CONTROL ROOMS (IFC 605.3.1)

- A. WHERE RATED ASSEMBLIES ARE SHOWN ON THE FLS PLAN, PROVIDE A UL OR GA LISTED RATED ASSEMBLY TO MEET THE FIRE RATING REQUIREMENTS TO THE ARCHITECT FOR
- B. PROVIDE A UL OR GA LISTED PERIMETER JOINT ASSEMBLY AND THROUGH PENETRATION FIRE STOP ASSMEMBLY MEETING THE FIRE RATED REQUIREMENT OF THE WALL,
- C. PROVIDE A SUBMITTAL CUTSHEET TO THE ARCHITECT OF EACH SELECTED FIRE

- A. MEANS OF EGRESS, INCLUDING EXIT DISCHARGE, SHALL BE ILLUMINATED AT ALL TIMES
- B. PROVIDE MINIMUM 1 FOOT-CANDLE OF ILLUMINATION AT ALL MEANS OF EGRESS. THE POWER SUPPLY FOR THE MEANS OF EGRESS ILLUMINATION SHALL NORMALLY BE PROVIDED BY THE BUILDINGS ELECTRICAL SUPPLY. IN THE EVENT OF A POWER FAILURE, THE EMERGENCY POWER SHALL PROVIDE POWER FOR A DURATION OF NOT LESS THAN 90 MINUTES AND SHALL CONSIST OF STORAGE BATTERIES, UNIT EQUIPMENT, OR AN ON-SITE GENERATOR. THE INSTALLATION OF THE EMERGENCY POWER SYSTEM SHALL BE IN ACCORDANCE WITH 2015 IBC SECTION 2702 AND 2015 IBC SECTION 1006.
- C. PRIOR TO FINAL INSPECTION, SUBMIT DOCUMENTATION SUBSTANTIATING THE COMPLETION OF TEST FOR THE MEANS OF EGRESS ILLUMINATION LEVEL PER 2015 IBC 1008.2.1, 1008.3 AND EMERGENCY POWER PER 1008.3.5.

DELEGATED DESIGN SUBMITTALS/PERMITS

- A TITEMS LISTED AS A DEFERRED SUBMITTAL OR DESIGN BUILD ITEMS ON SHEET GOOT REQUIRE ENGINEERING TO BE PROVIDED BY THE GENERAL CONTRACTOR.
- CONTAINED WITHIN THESE CONTRACT DOCUMENTS. PROVIDE A SUBMITTAL TO THE ARCHITECT FOR REVIEW OF DESIGN INTENT CONFORMANCE ONLY; THIS REVIEW DOES NOT CONSTITUTE A PROFESSIONAL PEER REVIEW OF THE SYSTEMS SUBMITTED.
- C. WHERE A LICENSED DESIGN PROFESSIONAL IS REQUIRED BY THE AUTHORITY HAVING JURISDICTION, THE GENERAL CONTRACTOR IS TO SECURE THESE SERVICES AND PROVIDE STAMPED DOCUMENTS TO MEET THE LOCAL REQUIREMENTS FOR A DEFERRED
- D. ADDITIONAL DEFERRED SUBMITTAL OR PERMIT FEES TO BE PAID BY THE GENERAL

ORS 447.241 (25% ADA RULE) COMPLIANCE EVERY PROJECT FOR RENOVATION, ALTERATION OR MODIFICATION TO AFFECTED

OR ACCESS TO AN AREA CONTAINING A PRIMARY FUNCTION SHALL BE MADE TO INSURE THAT, TO THE MAXIMUM EXTENT FEASIBLE, THE PATHS OF TRAVEL TO THE ALTERED AREA AND THE RESTROOMS. TELEPHONES AND DRINKING FOUNTAINS SERVING THE ALTERED AREA ARE READILY ACCESSIBLE TO AND USEABLE BY INDIVIDUALS WITH DISABILITIES, UNLESS SUCH ALTERATIONS ARE DISPROPORTIONATE TO THE OVERALL ALTERATIONS IN

OR ELEMENTS SERVING THE ALTERED AREA PROPOSED TO BE REMEDIATED WITHIN THIS NEW ACCESSIBLE PARKING SIGANGE & PAVEMENT MARKINGS TO MEET CURRETN REQUIREMENTS AT EXISTING ADA PARKING ACCESS AISLE


FOLLOWING COMPLETION OF THIS PROJECT, NO ADDITIONAL BARRIERS ARE KNOWN


ODE SUMMAR	Y		
PPLICABLE CODE	<u>S</u>		
2021 OREGON STRUCTUR 2021 OREGON ENERGY EF 2019 OREGON MECHANICA	FICIENCY SPECIALT	E (OSSC) Y CODE (OEEISC)	
2021 OREGON PLUMBING 2021 OREGON ELECTRICA 2019 OREGON FIRE CODE ICC/ANSI A117.1 - 2017	SPECIALTY CODE (O L SPECIALTY CODE		
CITY OF BEAVERTON MUN	ICIPAL CODE		
ONSTRUCTION TY	<u>/PE & USE (C</u>	HAPTERS 3,4 &	<u>5)</u>
BUILDING OCCUPANCY: CONSTUCTION TYPE:	B (OFFICE), A-3 (A)	SSEMBLY) D) - FORMERLY JI-1 HR 199	3 OSSC/ 1991 UBC
STORIES: EXISTING FLOOR AREA:	3 STORIES ABOVE 74,824 SF	GRADE	
LEVEL 1: LEVEL 2: LEVEL 3:	24,971 SF 24,722 SF 25,081 SF		
EXISTING HEIGHT: SEPARATION:	39'-6" AFF NON-SEPARATED	OCCUPANCIES	
	OR PUBLIC RIGHT	ING IS FULLY SURROUNDE OF WAY IN ACCORDANCE MUM FRONTAGE INCREAS	WITH SECTION
IRE-RESISTANT R		DR A-3 OCCUPANCY/WORS	
PRIMARY STRUCTURAL FI		0 HOURS	
BEARING WALLS: EXTERIOR: INTERIOR:		0 HOURS 0 HOURS	
NON BEARING WALLS AND EXTERIOR: INTERIOR:	PARTITIONS:	SEE SHELL FLS PLANS	
FLOOR CONSTRUCTION: ROOF CONSTRUCTION:		0 HOURS 0 HOURS	
ITERIOR FINISHES	<u>S (CHAPTER</u>	<u>8)</u>	
ALL INTERIOR AND CEILIN ASTM E84 OR UL 723 AND I BY TABLE 803.9 BELOW:			
INTERIOR EXIT STAIRWAY: CORRIDORS AND ENCLOS ROOMS AND ENCLOSED S	UES FOR EXIT STAIF		CLASS A CLASS B CLASS C
IEANS OF EGRESS		<u>_</u>	
SUITE IF THE OVERALL OC	CUPANT LOAD IS GI	REATER THAN 49	
TRAVEL FOR OCCUPANCY AUTOMATIC SPRINKLER S	GROUPS B SHALL N YSTEM IN ACCORDA	NOT BE MORE THAN 100 F INCE IWTH 903.3.1.1	EET WITH AN
1007.1.1 EXIT DISTANCE: V SHALL NOT BE LESS THAN SYSTEM.			
1016.2 EXIT TRAVEL DISTA Sprinklered: 300'	NCE: MAXIMUM TR	AVEL DISTANCE FOR OCC	UPANCY B,
1020.1 CORRIDOR FIRE-RE FOR OCCUPANCY TYPES E SYSTEM IN ACCORDANCE	FOR BUILDINGS EC		
XISTING BUILE		PLIANCE (IEB	C)
THE FOLLOWING ITEMS DESC THE PROJECT TO MEET CHAR NTERNATIONAL BUILDING CO SPECIALTY STRUCTURAL CO	PTER 3 AND CHAPTE DDE REFERENCED T	R 5 REQUIREMENTS OF TH	HE 2018
HAPTER 3 - PR OMPLIANCE MI		FOR ALL	
HE FOLLOWING REQUIPMENT HANGES OF OCCUPANCY RE			DDITIONS AND
EXISTING MATERIALS (302 COMPLIANCE WITH THEIR UNLESS DETERMINED BY	TÍME OF INSTALLAT	ION SHALL BE PERMITTED	
NEW & REPLACEMENT MA CODES FOR NEW CONSTR ALTERNATIONS, LIKE MAT HAZARD TO LIFE, HEALTH	RUCTION SHALL BE U ERIALS TO EXISTING		PAIRS OR
ACCESSIBILITY FOR EXIST a. EXTENT OF APPLICAT EFFECT OF REDUCIN	TON (305.3) - ALTER/	5) - ATIONS SHALL NOT REDUC F A FACILITY OR PORTION	CE OR HAVE THE OF A FACILITY.
WHERE AN ALTERNA THE ROUTE TO THE P ROUTE TO THE PRIM/ FOUNTAINS SERVING	TION AFFECTS AN A PRIMARY FUNCTION ARY AREA SHALL ING THIS AREA. THE M SHALL NOT EXCEED	PRIMARY FUNCTIONS/20% REA CONTAINING A PRIMA SHALL BE ACCESSIBLE. T CLUDE TOILET FACILITIES AXIMUM COSTS OF PROVID 20% OF THE COSTS OF TH	RY FUNCTION, HE ACCESSIBLE AND DRINKING DING THE
HAPTER 5 - PR	ESCRIPTIN	VE COMPLIAN	ICE
HIS PROJECT PROPOSES USI HAPTER 5 OF THE 2018 INTER			
COMPLIANCE METHOD) O OF THIS PROJECT SHALL	F THE INTERNATION ALTER THE EXISTIN	NTS OF CHAPTER 5 (PRES IAL EXISTING BUILDING CC G BUILDING TO BECOME LI	DE. NO PORTION
	ERATIONS TO EXIST E FOR NEW CONSTR NTS - GRAVITY LOAI		RUCTURAL
OR WILL NEED TO BE b. STRUCTURAL ELEME	STRENGTHENED.	INALL NOT BE INCREASED DS - ADDITIONAL LOADS LI ING ELEMENTS MAY BE IG	ESS THAN 10% ON
. WINDOWS AND EMERGEN a. REPLACEMENT WIND OCCUPANCIES, WIND	ICY ESCAPE OPENIN OW OPENING CONT DOW OPENING CONT	IGS (505): ROL DEVICE (505.2) - WITH ROL DEVICES COMPLYING	IIN R-2 3 ASTM F2090
a. EMERGENCY ESCAPE	E AND RESCUE OPE SHALL BE OPERATIO	ig Window is Replaced. Nings (505.4) - Emergenc Nal From the Inside of	Y ESCAPE AND

D. CHANGE OF OCCUPANCY (506): a. NO CHANGES OF OCCUPANCY SHALL BE MADE UNLESS THAT BUILDING IS MADE TO COMPLY WITH THE REQUIREMENTS OF THE BUILDING CODE FOR THAT USE OR OCCUPANCY. CHANGES OF OCCUPANCY SHALL NOT MAKE THE BUILDING LESS COMPLIANT WITH CODE REQUIREMENTS THAN IT WAS PRIOR TO THE CHANGE.


LEGEND - FLS PLANS

CONSTRUCTION JOINTS A	OUS UL LISTED ASSEMBLIES FOR ALL ND THROUGH WALL PENETRATIONS MATCHING TING OF ALL WALLS INDICATED BELOW:
••••••	1/2 HOUR FIRE PARTITION - 20 MINUTE DOOR
	1 HOUR FIRE PARTITION - 45 MINUTE DOOR
	1 HOUR FIRE BARRIER - 60 MINUTE DOOR
— – – — – – –	2 HOUR FIRE BARRIER - 90 MINUTE DOOR
	• 3 HOUR FIRE BARRIER - 20 MINUTE DOOR
+	EGRESS PATH OF TRAVEL WITH MINIMUM CLEARANCE WIDTH INDICATED. PROVIDE MINIMUM ILLUMINATION FOR EXITING. - COMMON PATH OF EGRESS TRAVEL (OSSC 1014.
$\mathbf{F} - \frac{\hat{\mathbf{F}}}{\mathbf{E}} - \frac{\mathbf{F}}{\mathbf{F}} - \frac{\mathbf{F}}{\mathbf{F}}$	- EXIT ACCESS DISTANCE (OSSC 1016)
	OCCUPANT LOAD AT OPENING
	CUMMALTIVE OCCUPANT LOAD AT OPENING
	LIGHTED EXIT SIGN - CEILING MOUNTED SHADING INDICATES LIGHTED FACE(S), DIRECTIC ARROW CORRESPONDS TO DIRECTION ARROW (SIGN
Î A	LIGHTED EXIT SIGN - WALL MOUNTED
F.E.C	FIRE EXTINGUISHER CABINET - COORDINATE LOCATION WITH FIRE MARSHAL






(9)





1 DEMOPLAN - SECTOR A - GROUND LEVEL SCALE: 1/8" = 1'-0"


CLIENT BEAVERTON SCHOOL DISTRICT 1260 NW Waterhouse Avenue Beaverton, OR 97006 COPYRIGHT This drawing has been prepared solely for the intended use, thus any reproduction or distribution for any purpose other than authorized by Arcadis is forbidden. Written dimensions shall have precedence over scaled dimensions. Contractors shall verify and be responsible for all dimensions and conditions on the job, and Arcadis shall be informed of any variations from the dimensions and conditions shown on the drawing. Shop drawings shall be submitted to Arcadis for general conformance before proceeding with fabrication. Arcadis Architects (USA) Inc. ISSUES No. DESCRIPTION DATE BID SET 2023-04-21 KEYPLAN D С A В CONSULTANTS SEAL 4346 PORTLAND. OREG PRIME CONSULTANT ARCADIS 830 NE Holladay Street Portland, OR 97232, USA tel 503 226 6950 fax 503 273 9192 PROJECT BSD ADMIN OFFICE TENANT IMPROVEMENT 1260 NW WATERHOUSE AVE BEAVERTON, OR 97006 PROJECT NO: 142595 SHEET TITLE ARCHITECTURAL DEMOLITION PLANS SHEET NUMBER AD1201




 DIMENSIONS SHOWN ARE TO FACE OF STUD. FACE OF MASONRY OR DETERINE OF COLUMN OR GRD UNE UNESS OF CHETERINES EDITERINE OF COLUMN OR GRD UNE UNESS OF CHETERINES SHOWN OR LOCATED VICE MORE UNESS OF CHETERINE ACTUAL ROUGH OPENING MASONRY DIMENSIONS. DIMENSIONS AT GLAZING ASSEMBLIES ARE TO CENTER OF ASSEMBLY UNLESS NOTED OTHERWISE. USE DIMENSIONS SHOWN, IN NO CASE SHALL WORKING DIMENSIONS SCALED FROM DRAWINGS. CROSS OFFECT DETAILS AND DIMENSIONS ON ARCHITECTURAL DRAWINGS WITH RELATED REQUIREMENTS ON STRUCTURAL, MECHANICAL, ELECTRICAL, PLUMBING, AND OTHER DR. AS APPLICABLE. NOTIFY ARCHITECT OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK. CONDITIONS AND DETAILS WHARED TYPICAL'S HALL APPLY IN ALL OF CONSTRUCTION AND DETAILS. WHERE NO SPECIFIC DETAIL SHOW CONSTRUCTION SHOLL BE IDENTICAL. OR SIMILARY TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC STANDARDS ARE APPLIED TO A MATERIAL OR MIL OF CONSTRUCTION TO BE USED ON THE WORK, ALL SUCH MATERIAL. METHODS ARE TO MANTAIN STANDARDS OF THE INDUSTRY AND, WHI APPLICABLE, MANUFACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION TO BE USED ON THE WORK, ALL SUCH MATERIAL. METHODS ARE TO MANTAIN STANDARDS OF THE INDUSTRY AND, WHI APPLICABLE, HANDYERY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBER AND WITH APPROPRIATE TRAD DRAWINGS. AND SUBCONTRACTORS FIRICATO CONSTRUCTION. COMFIRM ALL ROUGH OPENING SHOUND WITH APPROPRIATE TRAD DRAWINGS. AND AND AND AND AND AND AND AND AND AND	2.	CENTERLINE O DOORS NOT LC	F COLUMN OR GRID LINE UNLESS NOTED OTHERWISE.
 DOORS NOT LOCATED BY DIMENSION ARE TO BE CENTERED IN WALLS SHOWN OR LOCATED 41/2F (ROM FAGE OF STUD TO FACE OF AMB. MASONRY DIMENSIONS ARE NOMINAL. COORDINATE ACTUAL ROUGH OPENING MASONRY DIMENSIONS. DIMENSIONS AT GLAZING ASSEMBLIES ARE TO CENTER OF ASSEMBLY UNLESS NOTED OTHERWISE. USE DIMENSIONS SHOWN; IN NO CASE SHALL WORKING DIMENSIONS SCALED FROM DRAWINGS. CROSS CHECK DETAILS AND DIMENSIONS ON ARCHITECTURAL DRAWINGS WITH RELATED REQUIREMENTS ON STRUCTURAL, MECHANICAL, ELECTRICAL, PLUMBING, AND OTHER DR. AS APPLICABLE. NOTIFY ARCHITECT OF ANY DISCREPANCIES BEFORE PROCEEDING WITH HEW VORK. CONDITIONS AND DETAILS MARKED TYPICAL "SHALL APPLY IN ALL CA UNLESS SPECIFICALLY INDICATED OTHERWISE: TYPICAL DETAILS NOT REFERENCED ON DRAWINGS APPLY UNLESS NOTED OTHER WISE BY SPECIFIC NOTES AND DETAILS. WHERE NO SPECIFIC DETAIL IS SHOW CONSTRUCTION SHALL BE IDENTICAL OR SIMILAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OTHER PROJECT. WHERE NO SPECIFIC STANDARDS ARE APPLIED TO A MATERIAL. OR MI OF CONSTRUCTION TO BE USED OT THE WORK, ALL SUCH MATERIAL. METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND. WHI APPLICABLE, MANURACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NOCESSARY ANCHORAGE BLOCKING, BACKING, RAALIN HANDRAILS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COI INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION, BACKER BOARD BARD TO TEMPLICULAR TO A DASS STUDENT, AND ALL OTHER ITEMS AS REDUIRED COLCATION AND RESTRODUCLA SHALL SARE NOT TAGED, SLOW CONS, KITCHEN ARAS, SHEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BARD DARI M		DOORS NOT LC	
 SHOWN OR LOCATED 4 12" FROM FACE OF STUD TO FACE OF JAME. MASONRY DIMENSIONS ARE NOMINAL. COORDINATE ACTUAL ROUGH OPENING MASONRY DIMENSIONS. DIMENSIONS AT CLAZING ASSEMBLIES ARE TO CENTER OF ASSEMBLY. UISE DIMENSIONS AST CLAZING ASSEMBLIES ARE TO CENTER OF ASSEMBLY. UISE DIMENSIONS AST CLAZING ASSEMBLIES ARE TO CENTER OF ASSEMBLY. UISE DIMENSIONS AT CLAZING ASSEMBLIES ARE TO CENTER OF ASSEMBLY. UISE DIMENSIONS AST CLAZING ASSEMBLIES ARE TO CENTER OF ASSEMBLY. UISE DIMENSIONS AST CLAZING ASSEMBLIES ARE TO CENTER OF ASSEMBLY. UISE DIMENSIONS AND CHAIL ORAWINGS WITH RELATED REQUIREMENTS ON STRUCTURENT AND DETAILS MARKED 'TYPICAL' SHALL APPLY IN ALL CA UNLESS SPECIFICALLY INDICATED OTHERWISE. TYPICAL DETAILS SHOW CONSTRUCTION SAND DETAILS. WHERE NO SPECIFIC DETAIL IS SHOW CONSTRUCTION TO REAL DE IDENTICAL OR SMILLAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC STANDARDS ARE APPLIE INDUSTRY AND. WHI APPLICABLE. MANUFACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION OT THE RUDIS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND FLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDRALL, ELECTRICAL, AND FLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE SOLID BLOCKING BTOPS. CASEWORK SHELYING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR CO INSTALLATION. COMFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PROF TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAL MULTYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHER WALLATION. PROVIDE SOLID BLOCKING BETWEEN AS ADDUTIONAL INFORMATIO A CO			
 OPENING MASONRY DIMENSIONS. DIMENSIONS AT CLAZING ASSEMBLIES ARE TO CENTER OF ASSEMBLY UNLESS NOTEO OTHERWISE. USE DIMENSIONS AT CLAZING ASSEMBLIES ARE TO CENTER OF ASSEMBLY UNLESS NOTEO OTHERWISE. USE DIMENSIONS AT CLAZING ASSEMBLIES ARE TO CENTER OF ASSEMBLY UNLESS NOTEO OTHERWISE ON STRUCTURAL MECHANICAL, ELECTRICAL, PLUMBING, AND OTHER DR. AS APPLICABLE. NOTIFY ARCHITECT OF ANY DISCREPANCIES BEFORE PROCECEDING WITH THE WORK. CONDITIONS AND DETAILS MARKED TYPICAL "SHALL APPLY IN ALL CA UNLESS SPECIFICALLY INDICATED OTHERWISE. TYPICAL DETAILS SHOW CONSTRUCTION SHALL BE IDENTICAL OR SMILLAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC STANDARDS ARE APPLIED TO A MATERIAL. OR MI OF CONSTRUCTION TO BE USED ON THE WORK, ALL SUCH MATERIAL. METHODS ARE TO MAINTAIN ISTANDARDS OF THE INDUSTRY AND. WHI APPLICABLE. MANUFACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND FLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION INSELLATION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BRACING, FRAMINH HANDRALL, ELECTRICAL, AND ALL OTHER ITEMS AS REQUIRED FOR CO IN INTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDD PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WA WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLD BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUND PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. PROVIDE SOLD BLOCKING BETWEEN ADD TIONAL INFORMATIO ONTED WALL SARE NOT TAGGED. ASSUME WALL TYPE ATA. FRAME 4 ASSE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE ADDITIONAL INFORMATION. SEE ELLARCED TOILET ROOM P			CATED 4 1/2" FROM FACE OF STUD TO FACE OF JAMB.
 DIMENSIONS AT GLAZING ASSEMBLIES ARE TO CENTER OF ASSEMBLY UNLESS NOTEO OTHERWISE. USE DIMENSIONS SHOWN: IN NO CASE SHALL WORKING DIMENSIONS SCALED FROM DRAWINGS. CROSS CHECK DETAILS AND DIMENSIONS ON ARCHITECTURAL DRAWINGS WITH RELATED REQUIREMENTS ON STRUCTURAL MECHANICAL, ELECTRICAL, PUNBING, AND OTHER DR. AS APPLICABLE. NOTIFY ARCHITECT OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK. CONDITIONS AND DETAILS MARKED TYPICAL: "SHALL APPLY IN ALL CA UNLESS SPECIFICALLY NDICATED OTHERWISE: TYPICAL: DETAILS NOT REFERENCED ON DRAWINGS APPLY UNLESS NOTED OTHERWISE BY SPECIFIC NOTES AND DETAILS. WHERE NO SPECIFIC DETAIL IS SHOW CONSTRUCTION SHALL BE IDENTICAL OR SIMILAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC STANDARDS ARE APPLIED TO A MATERIAL OR MI OF CONSTRUCTION TO BE USED ON THE WORK, ALL SUCH MATERIAL METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND, WH APPLICABLE, MANUFACTURING INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SOULARE FOOT. ESTABLISH AND VERNY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, MERKING, FRAMIN HANDRALS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER TIEMS AS REQUIRED FOR COI INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDD PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERRECTED BY PERPENDICULAR WAL MALL TYPE TO BE CONTINUOUS ENTREMOR CHOOS AND WINDD PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERRECTED BY PERPENDICULAR WAL MALL TYPE TO BE CONTINUOUS. FURNES SENTED TO TRADARI JOISTS. WHERE A LENGTH OF WALL IS INTERRECTED BY PERPENDICULAR WAL MALLATIONS. SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ANDERENT AND AND ALL	3.		
 USE DIMENSIONS SHOWN: IN NO CASE SHALL WORKING DIMENSIONS SCALED FROM DRAWINGS. CROSS CHECK DETAILS AND DIMENSIONS STRUCTURAL, MECHANICAL, LECTRICAL, PUMBING, AND OTHER DR. AS APPLICABLE. NOTIFY ARCHITECT OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK. CONDITIONS AND DETAILS MARKED 'TYPICAL' SHALL APPLY IN ALL CA UNLESS SPECIFICALLY INDICATED OTHERWISE. TYPICAL DETAILS NOW CONSTRUCTION SHALL BE IDENTICAL OR SIMILAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC DETAILS SHOW CONSTRUCTION SHALL BE IDENTICAL OR SIMILAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC STANDARDS AFT THOLA OR MI OF CONSTRUCTION TO BE USED ON THE WORK, ALL SUCH MATERIAL, METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND, WH APPLICABLE, MANUFACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDARLS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHEN TERMS AS REQUIRED FOR CO INISTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOT D COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAI WALLATION. PROVIDE SOLD BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUM PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE ALLING TH TAGGED, ASSUME WALL TYPE A1. FRAME & BASE FOR ALL LOCKERS, FLOOR FINISHE SETEND TO BASE 10. TRENOR FINISH FACE OF WALLS SINCED SONTED OT TERMINATE A' JOISTS. PROVIDE SOLD BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUM PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. PROVIDE SOLD BL	4.		
 SCALED FROM DRAWINGS. CROSS CHECK DETALS AND DIMENSIONS ON ARCHITECTURAL DRAWINGS WITH RELATED REQUIREMENTS ON STRUCTURAL, MECHANICAL, ELECTRICAL, PLUMBING, AND OTHER DR, AS APPLICABLE. NOTFY ARCHITECT OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK. CONDITIONS AND DETAILS MARKED "TYPICAL" SHALL APPLY IN ALL CA UNLESS SPECIFICALLY INDICATED OTHERWISE. TYPICAL DETAILS NOT REFERENCED ON DRAWINGS APPLY UNLESS NOTED OTHERWISE SY SPECIFIC NOTES AND DETAILS. WHERE NO SPECIFIC DETAIL IS SHOW CONSTRUCTION SHALL BEI DENTITCAL OR SIMULAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC STANDARDS ARE APPLED ON A MATERIAL OR MI OF CONSTRUCTION TO BE USED ON THE WORK, ALL SUCH MATERIAL. METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND. WHI APPLICABLE, MANUFACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCOMTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL INCESSARY ANCHORAGE BLOCKING, BRAKING, FRAMIN HANDRAILS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COI INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAL WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. WHORE A LENGTH OF WALL SINTERSECTED BY PERPENDICULAR WAL WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. WHERE A ALENGTH OF WALL SITTERSECTED BY PERPENDICULAR WAL WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. WHERE A LENGTH OF WALL SISTEMENT ON DARD IN ALL. RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE TO	F		
 STRUCTURAL, MECHANICAL, ELECTRICAL, PLUMBING, AND OTHER DR. AS APPLICABLE. NOTEY ARCHITECT OF ANY DISCREPANCES BEFORE PROCEEDING WITH THE WORK. CONDITIONS AND DETAILS MARKED "TYPICAL" SHALL APPLY IN ALL CAS UNLESS SPECIFICALLY INDICATED OTHERWISE. TYPICAL DETAILS NOT REFERENCEO ON DRAWINGS APPLY UNLESS NOTED OTHERWISE BY SPECIFIC NOTES AND DETAILS. WHERE NO SPECIFIC DETAIL IS SNOW CONSTRUCTION SHALL BE IDENTICAL OR SIMILAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC STANDARDS ARE APPLIED TO A MATERIAL OR MI OF CONSTRUCTION TO BE USED ON THE WORK, ALL SUCH MATERIAL. METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND, WHI APPLICABLE, MANUFACTURERS' INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DELIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DELIVE LOAD PER SQUARE FOOT. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BRAKING, MIRRORS WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COI INSTALLATION. CONFRIM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAI WALL TYPE TO ECONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE ALLS ARE NOT TAGGED, ASSUME WALL TYPE ATA. FRAME "A BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE ACHIEVE FUSH CONDITION FOR INTERIOR OFYPSUM BOARD. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. CUSTODIAL ROOMS, KITCHEN AREAS, SUSTODIAL ROOMS, KITCHEN AREAS, SUSTODIAL ROOMS, KITCHEN AREAS, SUSTODIAL ROOMS, KITCHEN AREAS, SUSTODIAL ASSEM	J.		
 AS APPLICABLE. NOTIFY ARCHITECT OF ANY DISCREPANCIES BEFORE PROCEEDING WITH THE WORK. CONDITIONS AND DETAILS MARKED "TYPICAL" SHALL APPLY IN ALL CA UNLESS SPECIFICALLY INDICATED OTHERWISE. TYPICAL DETAILS NOW SPECIFIC NOTES AND DETAILS. WHERE NO SPECIFIC DETAILS SHOW CONSTRUCTION SHALL BE IDENTICAL OR SIMILAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC STANDARDS ARE APPLIED TO A MATERIAL SA METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND. WHI APPLICABLE. MANUFACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIAL SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDRALS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR CO INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOVIDE SOLID BLOCKING BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN RAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROGF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A18. FRAME 45 BASE FOR ALL LOCKERS, LOOR FINISHES EXTEND TO BASE ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. WEER WALLS ARE NOT TAGGED, ASSUME WALL TYPE A18. FRAME 45 BASE FOR AULL IS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE ELARGED FOUNTAINS. PROVIDE BACKER BOARD BEHIND AUL WALL APPLICATIONS. AND DETAILS FOR ADDARD IN ALL INFORMATIO ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. SEE INTERIOR SETIONS FOR DOCATION AND EXTEND FOR MALES AND TO DEXTEND FOLL LEGANT MALL ASSEMBLIES UNCESS NOTED OTHER SEDIMENT FOR MALLS			
 PROCEEDING WITH THE WORK. CONDITIONS AND DETAILS MARKED "TYPICAL" SHALL APPLY IN ALL CA UNLESS SPECIFICALLY INDICATED OTHERWISE. TYPICAL DETAILS NOT REFERENCED ON DRAWINGS APPLY UNLESS NOTED OTHERWISE SY PECIFIC NOTES AND DETAILS. WHERE NO SPECIFIC DETAIL IS SHOW CONSTRUCTION SHALL BE IDENTICAL OR SIMILAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC STANDARDS ARE APPLIED TO A MATERIAL OR MI OF CONSTRUCTION TO BE USED ON THE WORK, ALL SUCH WATERIAL. METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND, WHI APPLICABLE, MANUFACTURERS INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND FLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BRAWIN MONTALLS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTALLS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MURRAL, SARE NOT TAGED, ASSUME WALL TYPE ALL STALLATION. CONTINUOUS ENTICENT ACGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGED, ASSUME WALL TYPE ATA. FRAME & BASE FOR ALL LOCKERS, FLOOR FINSISTES SETTIOD TO BASE 1. TRENOR LEVACTIONS, FOR LOCATION OF SLAB EDGES.			
 UNLESS SPECIFICALLY INDICATED OTHERWISE. TYPICAL DETAILS NOT REFERENCED ON DRAWINGS APPLY UNLESS NOTED OTHERWISE BY SPECIFIC NOTES AND DETAILS. WHERE NO SPECIFIC DETAIL IS SHOW CONSTRUCTION SHALL BE IDENTICAL OR SIMILAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC STANDARDS ARE APPLIED TO A MATERIAL OR MI OF CONSTRUCTION TO BE USED ON THE WORK, ALL SUCH MATERIAL METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND, WHI APPLICABLE, MANUFACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDRALS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COT INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAI WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE AT JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4* BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERION FINISH FOR TAGGED, ASSUME WALL TYPE A1a. FRAME 4* BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE BEHIND ORINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. 		PROCEEDING V	VITH THE WORK.
 REFERENCED ON DRAWINGS APPLY UNLESS NOTED OTHERWISE BY SPECIFIC NOTES AND DETAILS. WHERE NO SPECIFIC DETAIL IS SHOW CONSTRUCTION SHALL BE IDENTICAL OR SIMILAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROLECT. WHERE NO SPECIFIC STANDARDS ARE APPLIED TO A MATERIAL OR METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND, WHI APPLICABLE, MANUFACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDRALS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COI INSTALLATION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAI WALL TYPE TO BE CONTINUOUS BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4' BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO EASISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4' BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS, FURR-OUT WALLS 'ACHEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD TO TERMINATE A' JOISTS. WHELE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4' BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS, FURR-OUT WALLS ' ACHEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. 	6.		
 CONSTRUCTION SHALL BE IDENTICAL OR SIMILAR TO THAT INDICATED THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC STANDARDS ARE APPLIED TO A MATERIAL OR MI OF CONSTRUCTION TO BE USED ON THE WORK, ALL SUCH MATERIAL METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND, WHI APPLICABLE, MANUFACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDRAILS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COI INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WA WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGED, ASSUME WALL TYPE A1a. FRAME "& BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS' ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. FREE NONS FACE OF WALLS SALL EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS' ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. SEE ELABRED TO LET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WETLE UNCLOSS, SAND DELEGATED DE OR ODOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE FINISHES. MOTED WALL SPENTOR OR ROOT ADDITIONAL INFORMATIO 2. ASSEMBLIES FOR WALLS S			
 THE TYPICAL CONSTRUCTION OF THE PROJECT. WHERE NO SPECIFIC STANDARDS ARE APPLIED TO A MATERIAL OR MI OF CONSTRUCTION TO BE USED ON THE WORK, ALL SUCH MATERIAL METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND, WHI APPLICABLE, MANUFACTURER'S INSTRUCTIONS. LOADDING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY AND PLOYENCE OCINIC, BACKING, FRAMIN HANDRAILS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COI INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WA WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE AT a 15. FRAME 4' BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE 16. INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS' ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOLET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ELABRED TOLET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. 			
 WHERE NO SPECIFIC STANDARDS ARE APPLIED TO A MATERIAL OR MI OF CONSTRUCTION TO BE USED ON THE WORK, ALL SUCH MATERIAL, METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND, WHI APPLICABLE, MANUFACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDRAILS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COI INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WA WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4' BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS' ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. SEEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL APPLICATIONS. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. MOTED WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS STANT GYPSUM BOARD ON ALL WALLS OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES NOTED OTHER SEE INTERIOR ELEVATIONS FOR DOCATION AND EXTENT OF APPLIED FINISHES. MOTED WALLS ATHOL SCATION AND EXTENT OF APPLIED FINISHES. MOT			
 METHODS ARE TO MAINTAIN STANDARDS OF THE INDUSTRY AND, WHI APPLICABLE, MANUFACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDRAILS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COI INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WA WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4* BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS' ACHIEVE FLUSH CONDITION FOR INTERIOR SPISUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND BRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WACELL TYPE DEPICTS TYPICAL WALL CONSTRUCTION SEE ELEVATIONS, SECTIONS, AND DETALS FOR ADDITONAL INFORMATIO 2. ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE 5. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW WALL APPELOATIONS. SEE SLAB PLAN FOR LOCATION FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHE	7.	WHERE NO SPE	ECIFIC STANDARDS ARE APPLIED TO A MATERIAL OR MI
 APPLICABLE, MANUFACTURER'S INSTRUCTIONS. LOADING OF CONSTRUCTION MATERIALS SHALL NOT EXCEED THE DE LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDRAILS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED FOUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COI INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WA WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHCHE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4* BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE NACHEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOLTURE RESISTANT GYPSUM BOARD NALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WATED WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. METAL STUD DESIGN IS DELEGATED DENDERS OUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNDESS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. PROVIDE HILS ABOVE ACCESSIBLE CELLINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 PEET MEASURED HORIZON NOTED OTHERWISE. ALL OPENINGS SHALL EXTEND FOM STRUCT FLOOR DECK ABOVE ACCESSI			
 LIVE LOAD PER SQUARE FOOT. ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDRAILS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED FOUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COI INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAI WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4* BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS' ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO 2. ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR ABOY ENJORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. MOTHER SUCK BADRED BEHIND ALL CONSTRUCTION ALL SOFT HOOT DE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF FLOOR TO UNDERSIDE OF RORD ADD THERWISE SUDUES SOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. MOVIDE MOISTURE RESISTANT GYPSUM BOARD		APPLICABLE, M	ANUFACTURER'S INSTRUCTIONS.
 ESTABLISH AND VERIFY ALL OPENINGS AND INSERTS FOR ARCHITECT MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDRAILS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COI INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAI WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4' BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS, FURR-OUT WALLS' ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WOTED WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BELIND ALL CERAMIC TILE APPLICATION SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE R	8.		
 MECHANICAL, ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD DRAWINGS, AND SUBCONTRACTORS PRIOR TO CONSTRUCTION. PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDRAILS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COL INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WA WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4* BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS, FURR-OUT WALLS' ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE SOLID BLOCKING FERSISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO 2. ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OT FLOOR BOCK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE 3. SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. 4. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. 5. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. 6. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. 7. POVIDE MOISTUR	9.		
 PROVIDE ALL NECESSARY ANCHORAGE BLOCKING, BACKING, FRAMIN HANDRAILS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COI INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WA WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4" BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS' ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWE A REAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNDERS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. MOYIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRI		MECHANICAL, E	ELECTRICAL, AND PLUMBING WITH APPROPRIATE TRAD
 HANDRALLS, DOOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL MOUNTED EQUIPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR COT INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAI WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4' BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS' ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL APPLICATIONS, SHALL EXTEND TO DIMERSION BART OF APPLICATION SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. MOTED WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO 2. ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE TILE BACKER BOARD BEHIND DRINKING FOUN	10.		
 INSTALLATION. CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAI WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4" BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS' ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL STUD DESIGN IS CONTION OF SLAB EDGES. WALL STUD DESIGN IS DELEGATED DESIGN. SEE ENLARGED FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DAIL CERAMIC TILE APPLICATIC ASSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND FROM STRUCTI FOOMS FIRE RATED WALLS SHALL EXTEND FOR SUMTAINS. PROVIDE TILE BACKER BOARD BEHIND DAIL CERAMIC TILE APPLICATIC ASSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND FROM STRUCT FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUICODE. A TRATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURE		HANDRAILS, DO	OOR STOPS, CASEWORK, SHELVING, MIRRORS, WALL
 CONFIRM ALL ROUGH OPENING DIMENSIONS FOR DOORS AND WINDO PRIOR TO COMMENCEMENT OF CONSTRUCTION. WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAI WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4" BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO 2. ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE 3. SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. PROVIDE TULE BACKER BOARD BEHIND ALL CRAMIC TILE APPLICATIO ASSEMBLIES FOR INS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. PROVIDE TULE BACKER BOARD BEHIND ALL CRAMIC TILE APPLICATIO ASSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND FOR MOSTRUCT FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUINCED. PROVIDE THE BACKER BOARD BEHIND DRINKING FOUNTAINS. PROVIDE THE BACKER BOARD BEHIND DRINKING FOUNTAINS. PROVIDE THE BACKER BOARD BEHIND DRINKING FOUNTAINS. PROVIDE THER BACKER BOARD BEHIND DRINKING FOU			IPMENT, AND ALL OTHER ITEMS AS REQUIRED FOR CON
 WHERE A LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WALL WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4" BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS' ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND ALL EXTEND FOM STRUCTU A SSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND FROM STRUCTU FLOOR TO UNDERSIDE OF FILOOR OR COS ABOVE UNLESS SOTED OTHERWISE. PROVIDE HIE BACKER BOARD BEHIND ALL ERAMIC TILE APPLICATIC NOTED OTHERWISE. ALL OPENINGS SHALL EXTEND FROM STRUCTU FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTAS, KITCHEN AREAS AND BEHIND AND BERNEND FOR STRUCTU FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL EXTEND FROM STRUCTU FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL EXTEND FROM STRUCTU FLOOR TO UNDER	11.	CONFIRM ALL F	
 WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS NOTED OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE AT JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4" BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS, FURR-OUT WALLS ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE TIRE BACKER BOARD BEHIND DRINKING FOUNTAINS. PROVIDE THE BACKER BOARD BEHIND DRINKING FOUNTAINS. PROVIDE THRE BADER BOARD BEHIND ANLL EXTEND FROM STRUCTO FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL EXTEND FROM STRUCTO FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTHERS. PROVIDE HEBACKER BOARD BEHIND DRINKING FOUNTAINS. PROVIDE THE BACKER BOARD BEHIND ANLL EXTEND FROM STRUCTO FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL EXTEND FROM STRUCTO FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS S	10		
 OTHERWISE. PROVIDE SOLID BLOCKING BETWEEN ROOF JOISTS WHERE WALL RUN PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4" BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS, FURR-OUT WALLS ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND ALL CERAMIC TILE APPLICATIC ASSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND TO NALL SYDTHERS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATIC ASSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND TO AN EXTEND FROM BY OTHERS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATIC ASSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND FROM STRUCTI FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUI CODE. A TRATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE AND/OR SMOKE BARRIER - PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICA	12.		
 PERPENDICULAR TO ROOF JOISTS. GYPSUM BOARD TO TERMINATE A' JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4" BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHER WETAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. PROVIDE TILE BACKER BOARD BEHIND DRINKING FOUNTAINS. PROVIDE HILES AND BEHIND ALL CERAMIC TILE APPLICATIOR A TRATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC IGINAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE RATED WALLS SHALL BE PROTECTED AS REQUINGED. PROVIDE FILE BACKER BOARD BEHIND ANLE SHALL BE PROTECTED AS REQUINGED. OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUINGED. ONDE FILE BACKER BOARD BEHIND ANLE SHALL BEPROTECTED AS REQUINGED. PROVIDE FILE BACKER BOARD BEHIND ANLE BEPROTECTED AS REQUINGED. PROVIDE FILE BACKER BOARD BEHIND ANLE BEPROTECTED AS REQUINGED. ON		OTHERWISE.	
 JOISTS. WHERE WALLS ARE NOT TAGGED, ASSUME WALL TYPE A1a. FRAME 4" BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHER SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF TROOMS, KITCHEN AREAS AND BEHIND ALL CERAMIC TILE APPLICATION. SEE NTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. A ROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF TROOMS, KITCHEN AREAS AND BEHIND ALL CERAMIC TILE APPLICATIO ASSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND FOUNTAINS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF TROOMS, KITCHEN AREAS AND BEHIND ALL CERAMIC TILE APPLICATIONS BY OTHERS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATIONS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATIONS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATIONS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATIONS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATIONS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATIONS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATIONS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE A	13.		
 FRAME 4" BASE FOR ALL LOCKERS, FLOOR FINISHES EXTEND TO BASE INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS ACHEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. MOTED WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATI INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE TILE BACKER BOARD BEHIND DRINKING FOUNTAINS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE TILE BACKER BOARD BEHIND DRINKING FOUNTAINS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATION FLOOR DECK ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUINCED. RATATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUINCED. AT RATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING 'FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENINGG PROVIDE FIRE BLOCKING IN CONCEALED SPACES OF STUD WALLS AND HORIZONTALLY AT INTERVALS NOT EXCEEDING 10 FEET. WHERE LENGTH OF WALL IS INTERSECTED BY PREPREDICULAR WALL WALL TYPE TO BE CONTINUOUS		JOISTS.	
 INTERIOR FINISH FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. MOTED WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE TILE BACKER BOARD BEHIND DRINKING FOUNTAINS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATIO TO EXTERD OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUI CODE. AT RATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE ANTED WALLS SHALE EXTEND FROM STRUCT FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUI CODE. AT RATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENING PARTITIONS VERTICALLY AT THE CEILING AND FLOOR L			
 ACHIEVE FLUSH CONDITION FOR INTERIOR GYPSUM BOARD. PROVIDE MOISTURE RESISTANT GYPSUM BOARD IN ALL TOILET ROOM RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE GENERRAL NOTES: NOTED WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE TILE BACKER BOARD BEHIND DRINKING FOUNTAINS. PROVIDE TIRE BACKER BOARD BEHIND DRINKING FOUNTAINS. PROVIDE TIRE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATION ASSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND FROM STRUCTI FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUINED CODE. AT RATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENINGS PROVIDE FIRE BLOCKING IN CONCEALED SPACES OF STUD WALLS AND HORIZONTALLY AT INTERVALS NOT EXCEEDING 10 FEET. WHERE LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAL WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS 		INTERIOR FINIS	H FACE OF WALLS IS CONTINUOUS. FURR-OUT WALLS
 RESTROOMS, SHOWER AREAS, CUSTODIAL ROOMS, KITCHEN AREAS, BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE GENERAL NOTES: NOTED WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTH SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAW BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND ALL EXTEND FOONTALINS. PROVIDE TILE BACKER BOARD BEHIND ANL EXTEND FROM STRUCTUR ASSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND FROM STRUCTUR FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL EXTEND FROM STRUCTUR FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL EXTEND FROM STRUCTUR FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUIN CODE. AT RATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZOON INDICATING "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENINGS PROVIDE FIRE ELENGTH OF WALL SI INTERSECTED BY PERPENDICULAR WALL WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS 	17		
 BEHIND DRINKING FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL WALL APPLICATIONS. 18. SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. 19. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO 2. ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHER SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. 4. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. 5. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATION. 6. PROVIDE TILE BACKER BOARD BEHIND DRINKING FOUNTAINS. 6. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATION. 7. ASSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND FOUNTAINS. 6. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATION. 7. ASSEMBLIES FOR FIRE RATED WALLS SHALL EXTEND FROM STRUCTI FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUINATIONS. 8. AT RATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENINGONS 9. PROVIDE FIRE BLOCKING IN CONCEALED SPACES OF STUD WALLS AND HORIZONTALLY AT INTERVALS NOT EXCEEDING 10 FEET. 10. WHERE LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WALL WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS	17.		
 SEE ENLARGED TOILET ROOM PLANS AND VERTICAL CIRCULATION PL FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHER SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND ALL CERAMIC TILE APPLICATIO FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL EXTEND FROM STRUCTI FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE AND/OR SMOKE BARRIER - PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENINGS PROVIDE FIRE BLOCKING IN CONCEALED SPACES OF STUD WALLS AND HORIZONTALLY AT INTERVALS NOT EXCEEDING 10 FEET. WHERE LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WALL WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS 		BEHIND DRINKI	NG FOUNTAINS. PROVIDE BACKER BOARD BEHIND ALL
 FOR MORE INFORMATION. SEE SLAB PLAN FOR LOCATION OF SLAB EDGES. WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATION FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUI CODE. AT RATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENINGS PROVIDE FIRE BLOCKING IN CONCEALED SPACES OF STUD WALLS AND HORIZONTALLY AT INTERVALS NOT EXCEEDING 10 FEET. WHERE LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WALL WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS 	18	-	
 NOTED WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND ALL CERAMIC TILE APPLICATION , KITCHEN AREAS AND BEHIND ALL CERAMIC TILE APPLICATION FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQUINCODE. AT RATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENINGS PROVIDE FIRE BLOCKING IN CONCEALED SPACES OF STUD WALLS AND PARTITIONS VERTICALLY AT THE CEILING AND FLOOR LEVELS AND HORIZONTALLY AT INTERVALS NOT EXCEEDING 10 FEET. WHERE LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WALL WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS 		FOR MORE INFO	ORMATION.
 NOTED WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OF FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATIO TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQU CODE. AT RATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENINGS PROVIDE FIRE BLOCKING IN CONCEALED SPACES OF STUD WALLS AND HORIZONTALLY AT INTERVALS NOT EXCEEDING 10 FEET. WHERE LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAL WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS 	19.	SEE SLAB PLAN	I FOR LOCATION OF SLAB EDGES.
 NOTED WALL TYPE DEPICTS TYPICAL WALL CONSTRUCTION. SEE ELEVATIONS, SECTIONS, AND DETAILS FOR ADDITIONAL INFORMATIO ASSEMBLIES FOR WALLS SHALL EXTEND TO UNDERSIDE OF ROOF OI FLOOR DECK ABOVE UNLESS NOTED OTHERWISE. SOUND BATT INSU TO EXTEND FULL HEIGHT IN WALL ASSEMBLIES UNLESS NOTED OTHE SEE INTERIOR ELEVATIONS FOR LOCATION AND EXTENT OF APPLIED FINISHES. METAL STUD DESIGN IS DELEGATED DESIGN. SEE METAL STUD DRAV BY OTHERS. PROVIDE MOISTURE RESISTANT GYPSUM BOARD ON ALL WALLS OF ROOMS, KITCHEN AREAS AND BEHIND DRINKING FOUNTAINS. PROVIDE TILE BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATION FLOOR TO UNDERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC NOTED OTHERWISE. ALL OPENINGS SHALL BE PROTECTED AS REQU CODE. AT RATED WALLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC SIGNAGE, SPACED AT NOT MORE THAN 30 FEET MEASURED HORIZON INDICATING "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENING PROVIDE FIRE BLOCKING IN CONCEALED SPACES OF STUD WALLS AND HORIZONTALLY AT INTERVALS NOT EXCEEDING 10 FEET. WHERE LENGTH OF WALL IS INTERSECTED BY PERPENDICULAR WAL WALL TYPE TO BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS 			
	6. 7.	ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UNI NOTED OTHEF CODE.	HEN AREAS AND BEHIND DRINKING FOUNTAINS. BACKER BOARD BEHIND ALL CERAMIC TILE APPLICATIO OR FIRE RATED WALLS SHALL EXTEND FROM STRUCT DERSIDE OF FLOOR OR ROOF ABOVE UNLESS SPECIFIC WISE. ALL OPENINGS SHALL BE PROTECTED AS REQU LLS ABOVE ACCESSIBLE CEILINGS, PROVIDE IDENTIFIC CED AT NOT MORE THAN 30 FEET MEASURED HORIZON
SMALL SPECKLED WHITE, 12 X 12	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED.	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS EGEND HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610
,	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED.	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS EGEND HES: CARPET TILE
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS EGEND HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING
	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING
B-14" RUBBER BASE, DARK GRAY TO MATCH EXISTINGB-24" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1 B-2	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES:	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1 B-2 WALL FINISH	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL DE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS ECONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES:
B-14" RUBBER BASE, DARK GRAY TO MATCH EXISTINGB-24" RUBBER BASE, LIGHT GRAY TO MATCH EXISTINGWALL FINISHES:	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING
B-14" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTINGWALL FINISHES: P-1WHITE TO MATCH EXISTING	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1	BLOCKING IN CONCEALED SPACES OF STUD WALLS AI ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING BLUE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPF	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1	BLOCKING IN CONCEALED SPACES OF STUD WALLS AI ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING BLUE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1	BLOCKING IN CONCEALED SPACES OF STUD WALLS AI ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING BLUE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 LAMINATES:	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1 CT-2 LAMINATES:	BLOCKING IN CONCEALED SPACES OF STUD WALLS A ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPF QH35 6 X 6 LAMINATES: PL-1 WILSONART KENSINGTON MAPLE 10776	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1 CT-2 LAMINATES: PL-1	BLOCKING IN CONCEALED SPACES OF STUD WALLS A ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 8LUE TO MATCH EXISTING BLUE TO MATCH EXISTING BLUE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPF QH35 6 X 6 LAMINATES: PL-1 WILSONART KENSINGTON MAPLE 10776 PL-2 WILSONART BLACKBIRD 5024	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1 CT-2 LAMINATES: PL-1 PL-2	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CT-2 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPF QH35 6 X 6 CHAMINATES: PL-1 WILSONART KENSINGTON MAPLE 10776 PL-2 WILSONART BLACKBIRD 5024 PL-3 ALMOND	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LEE FLOOR FINISI CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1 CT-2 LAMINATES: PL-1 PL-2 PL-3	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPF QH35 6 X 6 LAMINATES: PL-1 WILSONART KENSINGTON MAPLE 10776 PL-2 WILSONART BLACKBIRD 5024 PL-3 ALMOND OTHER:	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINIS CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1 CT-2 LAMINATES: PL-1 PL-2 PL-3 OTHER:	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CT-2 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPF QH35 6 X 6 CT-2 LAMINATES: PL-1 PL-2 WILSONART KENSINGTON MAPLE 10776 PL-2 WILSONART BLACKBIRD 5024 PL-3 ALMOND OTHER: HPC-1 BLACK TO MATCH EXISTING	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINIS CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1 CT-2 LAMINATES: PL-1 PL-2 PL-3 OTHER: HPC-1	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING BLUE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPF QH35 6 X 6 WILSONART KENSINGTON MAPLE 10776 WILSONART KENSINGTON MAPLE 10776 WILSONART BLACKBIRD 5024 ALMOND BLACK TO MATCH EXISTING
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPP QH35 6 X 6 LAMINATES: PL-1 PL-3 ALMOND OTHER: HPC-1 HPC-1 BLACK TO MATCH EXISTING SSM-1 RESIN	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LEE FLOOR FINIST CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1 CT-2 LAMINATES: PL-1 PL-2 PL-3 OTHER: HPC-1 SSM-1	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE OMATCH EXISTING BLACK WILSONART KENSINGTON MAPLE 10776 WILSONART KENSINGTON MAPLE 10776 WILSONART BLACKBIRD 5024 ALMOND BLACK TO MATCH EXISTING RESIN
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 WILSONART KENSINGTON MAPLE 10776 PL-3 ALMOND OTHER: HPC-1 HPC-1 BLACK TO MATCH EXISTING SSM-1 RESIN CORNER GUARD: CORNER GUARD:	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LEE FLOOR FINIST CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1 CT-2 LAMINATES: PL-1 PL-2 PL-3 OTHER: HPC-1 SSM-1 CORNER GU/	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING BLUE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPP QH35 6 X 6 WILSONART KENSINGTON MAPLE 10776 WILSONART KENSINGTON MAPLE 10776 WILSONART BLACKBIRD 5024 ALMOND BLACK TO MATCH EXISTING RESIN
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPP QH35 6 X 6 LAMINATES: PL-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPP QH35 6 X 6 LAMINATES: PL-2 WILSONART KENSINGTON MAPLE 10776 PL-2 WILSONART BLACKBIRD 5024 PL-3 ALMOND OTHER: HPC-1 BLACK TO MATCH EXISTING SSM-1 RESIN CORNER GUARD: CG-1 42" L, 90 DEGREE	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LEE FLOOR FINIST CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1 CT-2 LAMINATES: PL-1 PL-2 PL-3 OTHER: HPC-1 SSM-1 CORNER GU/ CG-1	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL DE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING ES: WHITE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPP QH35 6 X 6 WILSONART KENSINGTON MAPLE 10776 WILSONART BLACKBIRD 5024 ALMOND BLACK TO MATCH EXISTING RESIN
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 VILSONART KENSINGTON MAPLE 10776 PL-2 WILSONART BLACKBIRD 5024 PL-3 ALMOND OTHER: HPC-1 HPC-1 BLACK TO MATCH EXISTING SSM-1 RESIN CORNER GUARD: CORNER GUARD: CG-1 42" L, 90 DEGREE	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LEE FLOOR FINIST CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1 CT-2 LAMINATES: PL-1 PL-2 PL-3 OTHER: HPC-1 SSM-1 CORNER GU/ CG-1	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL DE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 5ES: WHITE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPP QH35 6 X 6 WILSONART KENSINGTON MAPLE 10776 WILSONART BLACKBIRD 5024 ALMOND BLACK TO MATCH EXISTING RESIN
B-1 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING B-2 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING WALL FINISHES: P-1 WHITE TO MATCH EXISTING P-2 BLUE TO MATCH EXISTING P-3 BLACK CT-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAR WHITE QH63 6 X 6 CT-2 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPP QH35 6 X 6 LAMINATES: PL-1 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPP QH35 6 X 6 LAMINATES: PL-1 WILSONART KENSINGTON MAPLE 10776 PL-2 WILSONART BLACKBIRD 5024 PL-3 ALMOND OTHER: HPC-1 BLACK TO MATCH EXISTING SSM-1 RESIN CORNER GUARD: CG-1 42" L, 90 DEGREE	9. 10.	INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED. IISH LE FLOOR FINISI CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1 CT-2 LAMINATES: PL-1 PL-2 PL-3 OTHER: HPC-1 SSM-1 CORNER GU/ CG-1 CG-2	BLOCKING IN CONCEALED SPACES OF STUD WALLS AN ERTICALLY AT THE CEILING AND FLOOR LEVELS AND Y AT INTERVALS NOT EXCEEDING 10 FEET. TH OF WALL IS INTERSECTED BY PERPENDICULAR WAL D BE CONTINUOUS BETWEEN TAGS UNLESS OTHERWIS HES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12 4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING 55: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING BLUE TO MATCH EXISTING BLACK CERAMIC WALL TILE - DALTILE NATURAL HUES, PEAF WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEPP QH35 6 X 6 WILSONART KENSINGTON MAPLE 10776 WILSONART KENSINGTON MAPLE 10776 WILSONART BLACKBIRD 5024 ALMOND BLACK TO MATCH EXISTING RESIN ARD: 42" L, 90 DEGREE










	OOR P	LAN	GEN	IERA	L NO	TES
1.	DIMENSIONS S					
2.	CENTERLINE O DOORS NOT LO	CATED BY	DIMENSION	ARE TO BE	CENTERED	IN WALLS
3.	SHOWN OR LO MASONRY DIMI	ENSIONS A	RE NOMINAI			
4.	OPENING MASC DIMENSIONS A	T GLAZING	ASSEMBLIE	S ARE TO CE	ENTER OF A	SSEMBLY
5.	UNLESS NOTED	NS SHOWN	I; IN NO CAS			
	SCALED FROM ON ARCHITECT	URAL DRA	WINGS WITH	H RELATED F	REQUIREME	NTS ON
	STRUCTURAL, AS APPLICABLE	E. NOTIFY	ARCHITECT			
6.	PROCEEDING V CONDITIONS AI	ND DETAIL	S MARKED "			
	UNLESS SPECI	ON DRAWI	NGS APPLY	UNLESS NOT	ED OTHERV	VISE BY
	SPECIFIC NOTE CONSTRUCTIO	N SHALL B	E IDENTICAL	OR SIMILAR		
7.	THE TYPICAL C	ECIFIC STA	NDARDS AR	E APPLIED T		
	OF CONSTRUC METHODS ARE	TO MAINT	AIN STANDA	RDS OF THE		
8.	APPLICABLE, M	ONSTRUCT	ION MATER			THE DE
9.	LIVE LOAD PER ESTABLISH ANI	D VERIFY A	LL OPENING			
10	MECHANICAL, E DRAWINGS, AN	ID SUBCON	ITRACTORS	PRIOR TO C	ONSTRUCTI	ON.
10.	PROVIDE ALL N HANDRAILS, DO	DOR STOPS	S, CASEWOF	RK, SHELVING	G, MIRRORS	, WALL
	MOUNTED EQU INSTALLATION.	,				
11.	CONFIRM ALL F	IMENCEME	NT OF CONS	STRUCTION.		
12.	WHERE A LENG					
13.	OTHERWISE. PROVIDE SOLIE					
4.4	PERPENDICULA					
14. 15.	WHERE WALLS	E FOR ALL I	OCKERS, FI	LOOR FINISH	IES EXTEND	
16.	INTERIOR FINIS	H CONDITIO	ON FOR INTE	ERIOR GYPSI	JM BOARD.	
17.	PROVIDE MOIS RESTROOMS, S	SHOWER A	REAS, CUST	ODIAL ROOM	IS, KITCHEN	I AREAS,
10	BEHIND DRINKI	TIONS.				
18.	SEE ENLARGE	ORMATION				ATION PL
19.	SEE SLAB PLAN	N FOR LOC	ATION OF SL	AB EDGES.		
W	ALL TY	PF (·	GENE	RAI	NOT	FS
1.	NOTED WALL ELEVATIONS,	SECTIONS,	AND DETAIL	LS FOR ADDI	TIONAL INFO	ORMATIO
2.	ASSEMBLIES F	ABOVE UN	LESS NOTED	O OTHERWIS	E. SOUND B	ATT INSU
3.	TO EXTEND FU SEE INTERIOR					
			NS FOR LOC	CATION AND	EXTENT OF	APPLIED
4.	FINISHES. METAL STUD I					
4. 5.	METAL STUD I BY OTHERS. PROVIDE MOIS	DESIGN IS I STURE RES	DELEGATED	DESIGN. SE PSUM BOARE	E METAL ST D ON ALL WA	UD DRAV
5. 6.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE	DESIGN IS I STURE RES HEN AREAS BACKER B	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA	E METAL ST D ON ALL WA FOUNTAINS MIC TILE AF	UD DRAV ALLS OF 3. PPLICATIO
5.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS	UD DRAV ALLS OF PLICATIO STRUCT SPECIFIO
5. 6. 7.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE.	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C RWISE. ALL	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF TEND FROM VE UNLESS ROTECTED A	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIO AS REQU
5. 6.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C RWISE. ALL LLS ABOVI ACED AT NO	DELEGATED SISTANT GYF AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF FEND FROM VE UNLESS ROTECTED A FOROVIDE II MEASURED	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIO AS REQU DENTIFIO HORIZOI
5. 6. 7.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C RWISE. ALL LLS ABOV ACED AT NO IRE AND/O E BLOCKINO	DELEGATED SISTANT GYF AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA IN CONCEA	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF TEND FROM VE UNLESS ROTECTED A MEASURED DTECT ALL O S OF STUD N	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIO AS REQU DENTIFIO HORIZOI DPENING WALLS A
5. 6. 7. 8. 9.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C RWISE. ALL LLS ABOV ACED AT NO IRE AND/O E BLOCKINO ERTICALLY Y AT INTEF	DELEGATED SISTANT GYF AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB OT MORE TH R SMOKE BA IN CONCEA AT THE CEI RVALS NOT E	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF TEND FROM VE UNLESS ROTECTED A MEASURED DTECT ALL C S OF STUD V LOOR LEVEL 10 FEET.	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIO AS REQU DENTIFIC HORIZOI DENTIFIC HORIZOI DENTIFIC NALLS AI S AND
5. 6. 7. 8.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C RWISE. ALL LLS ABOV ACED AT NO CED AT NO ERTICALLY Y AT INTEF TH OF WAL	DELEGATED SISTANT GYF AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA S IN CONCEA AT THE CEI VALS NOT E L IS INTERS	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A MEASURED DTECT ALL C S OF STUD V OOR LEVEL 10 FEET. ERPENDICU	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIO AS REQU DENTIFIC HORIZOI DENTIFIC WALLS AI S AND LAR WAL
5. 6. 7. 8. 9.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C RWISE. ALL LLS ABOV ACED AT NO CED AT NO ERTICALLY Y AT INTEF TH OF WAL	DELEGATED SISTANT GYF AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA S IN CONCEA AT THE CEI VALS NOT E L IS INTERS	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A MEASURED DTECT ALL C S OF STUD V OOR LEVEL 10 FEET. ERPENDICU	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIO AS REQU DENTIFIC HORIZOI DENTIFIC WALLS AI S AND LAR WAL
5. 6. 7. 8. 9.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C RWISE. ALL LLS ABOV ACED AT NO CED AT NO ERTICALLY Y AT INTEF TH OF WAL	DELEGATED SISTANT GYF AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA S IN CONCEA AT THE CEI VALS NOT E L IS INTERS	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A MEASURED DTECT ALL C S OF STUD V OOR LEVEL 10 FEET. ERPENDICU	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIO AS REQU DENTIFIC HORIZOI DENTIFIC WALLS AI S AND LAR WAL
5. 6. 7. 8. 9.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C RWISE. ALL LLS ABOV ACED AT NO CED AT NO ERTICALLY Y AT INTEF TH OF WAL	DELEGATED SISTANT GYF AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA S IN CONCEA AT THE CEI VALS NOT E L IS INTERS	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A MEASURED DTECT ALL C S OF STUD V OOR LEVEL 10 FEET. ERPENDICU	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIO AS REQU DENTIFIC HORIZOI DENTIFIC WALLS AI S AND LAR WAL
5. 6. 7. 8. 9.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C RWISE. ALL LLS ABOV ACED AT NO CED AT NO ERTICALLY Y AT INTEF TH OF WAL	DELEGATED SISTANT GYF AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA S IN CONCEA AT THE CEI VALS NOT E L IS INTERS	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A MEASURED DTECT ALL C S OF STUD V OOR LEVEL 10 FEET. ERPENDICU	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIO AS REQU DENTIFIC HORIZOI DENTIFIC WALLS AI S AND LAR WAL
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C RWISE. ALL LLS ABOV ACED AT NO IRE AND/O E BLOCKINO ERTICALLY Y AT INTEP TH OF WAL D BE CONT	DELEGATED SISTANT GYF AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA IN CONCEA AT THE CEI VALS NOT E L IS INTERS INUOUS BET	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A MEASURED DTECT ALL C S OF STUD V OOR LEVEL 10 FEET. ERPENDICU	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIO AS REQU DENTIFIC HORIZOI DENTIFIC WALLS AI S AND LAR WAL
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED.	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C RWISE. ALL LLS ABOV ACED AT NO IRE AND/O E BLOCKINO ERTICALLY Y AT INTER TH OF WAL D BE CONT	DELEGATED SISTANT GYF AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA IN CONCEA AT THE CEI VALS NOT E L IS INTERS INUOUS BET	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A MEASURED DTECT ALL C S OF STUD V OOR LEVEL 10 FEET. ERPENDICU	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIO AS REQU DENTIFIC HORIZOI DENTIFIC WALLS AI S AND LAR WAL
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED.	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C RWISE. ALL LLS ABOV ACED AT NO IRE AND/O E BLOCKINO ERTICALLY Y AT INTER TH OF WAL D BE CONT	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA S IN CONCEA AT THE CEN VALS NOT E L IS INTERS INUOUS BET NUOUS BET NUOUS BET TILE AIN - MOSA	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING ECTED BY PI WEEN TAGS	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF TEND FROM VE UNLESS ROTECTED A S, PROVIDE II MEASURED DTECT ALL C S OF STUD V OOR LEVEL 10 FEET. ERPENDICU S UNLESS OT	UD DRAV
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED.	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C WISE. ALL LLS ABOV/ ACED AT NO IRE AND/O EBLOCKING ERTICALLY Y AT INTER TH OF WAL D BE CONT	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA S IN CONCEA (AT THE CER VALS NOTE IN INTERS INUOUS BET NUOUS BET NUOUS BET TILE AIN - MOSA SPECKLED W	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE LING AND FL EXCEEDING ECTED BY PI WEEN TAGS	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF TEND FROM VE UNLESS ROTECTED A S, PROVIDE II MEASURED DTECT ALL C S OF STUD N OOR LEVEL 10 FEET. ERPENDICU S UNLESS OT	UD DRAV
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED.	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C WISE. ALL LLS ABOV/ ACED AT NO IRE AND/O EBLOCKING ERTICALLY Y AT INTER TH OF WAL D BE CONT	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA OPENINGS IN CONCEA (AT THE CER VALS NOTE IN INTERS INUOUS BET VID TILE AIN - MOSA SPECKLED W ER BASE, DA	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING ECTED BY PI WEEN TAGS	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF TEND FROM VE UNLESS ROTECTED A S, PROVIDE II MEASURED DTECT ALL C S OF STUD V OOR LEVEL 10 FEET. ERPENDICU S UNLESS OT	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIC AS REQU DENTIFIC HORIZOI DPENING VALLS AI S AND LAR WAL THERWIS
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED. NOTED. FLOOR FINIS CPT-1 PT-1 B-1 B-1 B-2	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C WISE. ALL LLS ABOV/ ACED AT NO EBLOCKING ERTICALLY Y AT INTEP TH OF WAL D BE CONT EGGEI HES: CARPET PORCEL SMALL S 4" RUBB 4" RUBB	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA OPENINGS IN CONCEA (AT THE CER VALS NOTE IN INTERS INUOUS BET VID TILE AIN - MOSA SPECKLED W ER BASE, DA	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING ECTED BY PI WEEN TAGS	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF TEND FROM VE UNLESS ROTECTED A S, PROVIDE II MEASURED DTECT ALL C S OF STUD V OOR LEVEL 10 FEET. ERPENDICU S UNLESS OT	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIC AS REQU DENTIFIC HORIZOI DPENING VALLS AI S AND LAR WAL THERWIS
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED. NOTED. FLOOR FINIS CPT-1 PT-1 B-1	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C WISE. ALL LLS ABOVI CED AT NO EBLOCKING ERTICALLY Y AT INTEP TH OF WAL D BE CONT ES: WHITE T	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA OPENINGS IN CONCEA (AT THE CER VALS NOTE IN INTERS INUOUS BET VID TILE AIN - MOSA SPECKLED W ER BASE, DA	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING ECTED BY PI WEEN TAGS	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF TEND FROM VE UNLESS ROTECTED A S, PROVIDE II MEASURED DTECT ALL C S OF STUD V OOR LEVEL 10 FEET. ERPENDICU S UNLESS OT	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIC AS REQU DENTIFIC HORIZOI DPENING VALLS AI S AND LAR WAL THERWIS
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED. SCPT-1 PT-1 B-1 B-1 B-2 WALL FINISH P-1	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C WISE. ALL LLS ABOVI CED AT NO EBLOCKING ERTICALLY Y AT INTEP TH OF WAL D BE CONT ES: WHITE T	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA IN CONCEA AT THE CEN VALS NOT E L IS INTERS INUOUS BET VALS NOT E L IS INTERS INUOUS BET TILE AIN - MOSA SPECKLED W ER BASE, DA ER BASE, DA ER BASE, DA ER BASE, DA	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING ECTED BY PI WEEN TAGS	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF TEND FROM VE UNLESS ROTECTED A S, PROVIDE II MEASURED DTECT ALL C S OF STUD V OOR LEVEL 10 FEET. ERPENDICU S UNLESS OT	UD DRAV ALLS OF PPLICATIO STRUCT SPECIFIC AS REQU DENTIFIC HORIZOI DPENING VALLS AI S AND LAR WAL THERWIS
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED. NOTED. FLOOR FINIS CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C WISE. ALL LLS ABOVI ACED AT NO EBLOCKING ERTICALLY TAT INTER TH OF WAL D BE CONT	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA IN CONCEA AT THE CEN WALS NOT E L IS INTERS INUOUS BET TILE AIN - MOSA SPECKLED W ER BASE, DA ER BASE, DA ER BASE, DA ER BASE, DA ER BASE, DA ER BASE, DA	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING ECTED BY PI WEEN TAGS	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A , PROVIDE II MEASURED DTECT ALL C S OF STUD Y OOR LEVEL 10 FEET. ERPENDICU S UNLESS OT UNLESS OT	UD DRAW
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED. NOTED. FLOOR FINIS CPT-1 PT-1 B-1 B-2 WALL FINISH P-2 P-3	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C WISE. ALL LLS ABOVI ACED AT NO EBLOCKING ERTICALLY TAT INTER TH OF WAL D BE CONT	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA IN CONCEA AT THE CEN R SMOKE BASE IN CONCEA THE CONCEAN THE C	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING ECTED BY PI WEEN TAGS	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A , PROVIDE II MEASURED DTECT ALL O S OF STUD Y OOR LEVEL 10 FEET. ERPENDICU S UNLESS OT UNLESS OT	UD DRAV
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG" WALL TYPE TO NOTED.	DESIGN IS I STURE RES BACKER B FOR FIRE R DERSIDE C WISE. ALL LLS ABOVI CED AT NO EBLOCKING ERTICALLY TAT INTER TH OF WAL D BE CONT	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA IN CONCEA AT THE CEN R SMOKE BASE IN CONCEA THE L IS INTERS INUOUS BET TILE AIN - MOSA SPECKLED W ER BASE, DA ER BASE, DA ER BASE, DA ER BASE, DA ER BASE, DA C WALL TILE O MATCH EX C WALL TILE C WALL TILE	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE ILING AND FL EXCEEDING ECTED BY PI WEEN TAGS	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A , PROVIDE II MEASURED DIECT ALL O S OF STUD Y OOR LEVEL 10 FEET. ERPENDICU S UNLESS OT UNLESS OT COMATCH EX O MATCH EX O MATCH EX	UD DRAV
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED.	DESIGN IS I STURE RES BACKER B FOR FIRE R DERSIDE C WISE. ALL LLS ABOVI CED AT NO EBLOCKING ERTICALLY YAT INTER TH OF WAL D BE CONT	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA IN CONCEA AT THE CEN WALS NOT E L IS INTERS INUOUS BET TILE AIN - MOSA SPECKLED W ER BASE, DA ER BASE, DA ER BASE, DA ER BASE, LIA O MATCH EX O MATCH EX O MATCH EX C WALL TILE 20 MATCH EX C WALL TILE 20 MATCH EX C WALL TILE 20 MATCH EX C WALL TILE 21 C WALL	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARE CEILINGS ING AND FL EXCEEDING ECTED BY PI WEEN TAGS	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A , PROVIDE II MEASURED DIECT ALL O S OF STUD Y OOR LEVEL 10 FEET. ERPENDICU S UNLESS OT UNLESS OT COMATCH EX O MATCH EX O MATCH EX	UD DRAV
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED. FLOOR FINIS CPT-1 PT-1 B-1 B-2 WALL FINISH P-1 P-2 P-3 CT-1 CT-2 LAMINATES: PL-1 PL-2 PL-3	DESIGN IS I STURE RES BACKER B FOR FIRE R DERSIDE C WISE. ALL LLS ABOVI CED AT NO EBLOCKING ERTICALLY TAT INTER TH OF WAL D BE CONT	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA IN CONCEA AT THE CEN WALS NOT E L IS INTERS INUOUS BET TILE AIN - MOSA SPECKLED W ER BASE, DA ER BASE, DA ER BASE, DA ER BASE, LIA O MATCH EX O MATCH EX O MATCH EX C WALL TILE 20 MATCH EX C WALL TILE 20 MATCH EX C WALL TILE 20 MATCH EX C WALL TILE 21 C WALL	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARE CEILINGS ING AND FL EXCEEDING ECTED BY PI WEEN TAGS	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A , PROVIDE II MEASURED DIECT ALL O S OF STUD Y OOR LEVEL 10 FEET. ERPENDICU S UNLESS OT UNLESS OT COMATCH EX O MATCH EX O MATCH EX	UD DRAV
5. 6. 7. 8. 9. 10.	METAL STUD I BY OTHERS. PROVIDE MOIS ROOMS, KITCH PROVIDE TILE ASSEMBLIES F FLOOR TO UN NOTED OTHEF CODE. AT RATED WA SIGNAGE, SPA INDICATING "F PROVIDE FIRE PARTITIONS V HORIZONTALL WHERE LENG WALL TYPE TO NOTED.	DESIGN IS I STURE RES HEN AREAS BACKER B FOR FIRE R DERSIDE C WISE. ALL LLS ABOV/ ACED AT NO IRE AND/O EBLOCKING ERTICALLY Y AT INTEF TH OF WAL D BE CONT	DELEGATED SISTANT GYF S AND BEHIN OARD BEHIN ATED WALL OF FLOOR OF OPENINGS E ACCESSIB DT MORE TH R SMOKE BA IN CONCEA AT THE CEN WALS NOT E L IS INTERS INUOUS BET TILE AIN - MOSA SPECKLED W ER BASE, DA ER BASE, DA ER BASE, DA ER BASE, LIA O MATCH EX O MATCH EX O MATCH EX C WALL TILE 20 MATCH EX C WALL TILE 20 MATCH EX C WALL TILE 20 MATCH EX C WALL TILE 21 C WALL	DESIGN. SE PSUM BOARE ID DRINKING ND ALL CERA S SHALL EXT R ROOF ABO SHALL BE PF LE CEILINGS IAN 30 FEET ARRIER - PRO ALED SPACE LING AND FL EXCEEDING ECTED BY PI WEEN TAGS GLOBAL COI /HITE, 12 X 1 ARK GRAY TO GHT GRAY TO XISTING ISTING E - DALTILE N E - DALTILE N IGTON MAPL BIRD 5024	E METAL ST O ON ALL WA FOUNTAINS MIC TILE AF END FROM VE UNLESS ROTECTED A , PROVIDE II MEASURED DIECT ALL O S OF STUD Y OOR LEVEL 10 FEET. ERPENDICU S UNLESS OT UNLESS OT COMATCH EX O MATCH EX O MATCH EX	UD DRAV

 CORNER GUARD:


 CG-1
 42"

 CG-2
 42"
 42" L, 90 DEGREE 42" L, U SHAPE XX-X FINISH TAG




1 SOUTH ELEVATION - EXISTING SCALE: NTS





2 DETAIL - NEW LOUVER SCALE: 1 1/2" = 1'-0"





(13)

EXTERIOR ELEVATIONS NOTES: 1. HPC - HIGH PERFORMANCE COATING ON ALL EXPOSED STEEL. 2. NOT ALL MECHANICAL PLUMPING ELECTRICAL OF TECHNOLOGY EIXTURES.


 NOT ALL MECHANICAL, PLUMBING, ELECTRICAL OR TECHNOLOGY FIXTURES AND DEVICES ARE SHOWN. COORDINATE WITH MECHANICAL, PLUMBING, ELECTRICAL, AND TECHNOLOGY DRAWINGS FOR ADDITIONAL FIXTURES AND DEVICES.
 ALL EXTERIOR WINDOWS ARE STOREFRONT. PREFINISHED METAL FASCIAS, GUITTERS AND COPINGS, TYP

 ALL EXTERIOR WINDOWS ARE STOREFRONT.
 PREFINISHED METAL FASCIAS, GUTTERS AND COPINGS, TYP.
 REFERENCE ELEVATIONS FOR GENERAL HEIGHTS AND MATERIALS, SEE FLOOR PLAN FOR LENGTHS.






2-04-21 1-57-10 PN





FIN	SH LE	GEND
	FLOOR FINISH CPT-1 PT-1	ES: CARPET TILE PORCELAIN - MOSA GLOBAL COLLECTION, 75610 SMALL SPECKLED WHITE, 12 X 12
	B-1 B-2	4" RUBBER BASE, DARK GRAY TO MATCH EXISTING 4" RUBBER BASE, LIGHT GRAY TO MATCH EXISTING
	WALL FINISHE P-1 P-2 P-3	S: WHITE TO MATCH EXISTING BLUE TO MATCH EXISTING BLACK
	CT-1 CT-2	CERAMIC WALL TILE - DALTILE NATURAL HUES, PEA WHITE QH63 6 X 6 CERAMIC WALL TILE - DALTILE NATURAL HUES, PEI QH35 6 X 6
	LAMINATES: PL-1 PL-2 PL-3	WILSONART KENSINGTON MAPLE 10776 WILSONART BLACKBIRD 5024 ALMOND
	OTHER: HPC-1 SSM-1	BLACK TO MATCH EXISTING RESIN
	CORNER GUA CG-1 CG-2	RD: 42" L, 90 DEGREE 42" L, U SHAPE
XX-X	FINISH TAG	




١G	
١G	

, PEARL , PEPPER





Door and Frame Schedule													
		[Door		Р	anel		Frame			Assembly		
No.	Location	Width	Height	Туре	Material	Finish	Glazing	Туре	Material	Finish	Rating (minutes)	Hardware	Comments
A100A	CIRCULATION	3'-0"	7'-0"	A	SC	CLEAR	<>	1	HM	HPC-1	20 MIN	1	
A101A	ADA RESTROOM	3'-0"	7'-0"	A	SC	CLEAR	<>	1	HM		NA	2	
A102A	ADA RESTROOM	3'-0"	7'-0"	A	SC	CLEAR	<>	1	HM	HPC-1	NA	2	
A201A	BREAKROOM	3'-0"	7'-0"	В	AL	MFR	IT-1	1	HM	MFR	NA	3	
A201B	BREAKROOM	3'-0"	7'-0"	В	AL	MFR	IT-1	1	HM	MFR	NA	3	






EXISTING DOOR AND FRAME, NEW FRAMES TO MATCH EXISTING -

 WOOD TRIM PIECE TO MATCH EXISTING DOOR TRIM HOLLOW METAL FRAME,
 HPC, SEE DOOR & FRAME
 SCHEDULE FOR COLOR



CLIENT BEAVERTON SCHOOL DISTRICT 1260 NW Waterhouse Avenue Beaverton, OR 97006 COPYRIGHT This drawing has been prepared solely for the intended use, thus any reproduction or distribution for any purpose other than authorized by Arcadis is forbidden. Written dimensions shall have precedence over scaled dimensions. Contractors shall verify and be responsible for all dimensions and conditions on the job, and Arcadis shall be informed of any variations from the dimensions and conditions shown on the drawing. Shop drawings shall be submitted to Arcadis for general conformance before proceeding with fabrication. Arcadis Architects (USA) Inc. ISSUES No. DESCRIPTION DATE BID SET 2023-04-21 CONSULTANTS SEAL TERED " ARCHT 4346 PORTLAND, OREG PRIME CONSULTANT ARCADIS 830 NE Holladay Street Portland, OR 97232, USA tel 503 226 6950 fax 503 273 9192 PROJECT BSD ADMIN OFFICE TENANT IMPROVEMENT 1260 NW WATERHOUSE AVE BEAVERTON, OR 97006 PROJECT NO: 142595 SHEET TITLE DOOR & RELITE SCHEDULE & TYPES SHEET NUMBER A6101









PER ELEVATION



DEPTH = 1' - 11"

- COUNTER PER


CABINET LOCK PER ELEVATIONS

ADJUSTABLE SHELF, PL-3

PLASTIC LAMINATE PL-1, TYPICAL


ELEVATIONS

- B-1




DIMENSION POINTS "H" - HEIGHT OF CABINET VERIFY ALL WIDTHS GIVEN IN THE FIELD. SEE INTERIOR ELEVATIONS FOR DIRECTION OF CABINET DOOR SWINGS (DIRECTION OF DOOR SWINGS SHOWN ON THIS SCHEDULE ARE FOR INDICATING CABINET TYPE ONLY). WHERE ENDS OF COUNTERTOPS W/ SPLASH TERMINATES AT A WALL, 4. SPLASH IS TO RETURN ALONG END TO FRONT EDGE OF COUNTERTOP. WHERE ENDS AND SIDES OF CABINET ARE EXPOSED, END PANEL IS TO BE FACED TO MATCH FRONT OF CABINET. EXPOSED ENDS OF CABINETS TO HAVE 3" DEEP X 4" HIGH TOESPACE, TYP. SEE FINISH LEGEND FOR PLASTIC LAMINATE COLOR & TYPE. MATERIALS WHICH ARE IN SIMILAR LOCATIONS ARE NOT NOTED AT EVERY OCCURRENCE. SEE FINISH FLOOR PLANS, REFLECTED CEILING PLANS, INTERIOR ELEVATIONS AND FINISH LEGEND FOR ADDITIONAL FINISH INFORMATION. 10. PROVIDE BACKING AT WALL MOUNTED ITEMS. CASEWORK ADA CLEARANCES: FINISH FACE OF WALL 2'-0" MAX _____ FINISH FACE EQ EQ OF CABINET 4'-0" MIN **ACCESSIBLE BASE CABINET / SINK**

DIMENSIONS OF CABINET TYPES ARE GIVEN AS FOLLOWS:









PLUMBING SYMBOL LIST

Abbreviat	ions	<u>General</u>	
(A)	ABANDON IN PLACE		
AFF	ABOVE FINISHED FLOOR	$\left(\begin{array}{c} x \\ x \end{array}\right)$	DETAIL NUMBER AND SHEET LOCATION
AP	ACCESS PANEL	\bigcirc	
& A	AND AQUASTAT, ARCHITECT, ANCHOR, AMPHERE	$\langle \mathbf{x} \rangle$	KEYED NOTE
@	AT		RETED NOTE
BFF	BELOW FINISHED FLOOR		
BF			SECTION NUMBER AND SHEET LOCATION
BTUH BLDG	BRITISH THERMAL UNITS PER HOUR BUILDING		
CO	CLEANOUT		EXISTING WORK
CW	COLD WATER		
CD CONT.			
CONT. CFH	CONTINUATION CUBIC FEET PER HOUR		NEW WORK
CFS	CUBIC FEET PER SECOND		
(X)	DEMOLISH		PIPE OR CONDUIT BELOW GRADE
DN D	DOWN DRAIN		
DFU	DRAINAGE FIXTURE UNIT		
DWV	DRAINAGE, WASTE AND VENT		CONTINUATION
EWH	ELECTRIC WATER HEATER		
ELECT	ELECTRICAL EXISTING	•	EXTENT OF DEMOLITION
(E) EJ	EXPANSION JOINT		
FT	FEET		
FPS	FEET PER SECOND		PIPE BELOW GRADE
FFE F	FINISHED FLOOR ELEVATION FIRE, FAHRENHEIT		
FC	FLEXIBLE CONNECTOR	•	POINT OF CONNECTION
FL	FLOOR		
FCO	FLOOR CLEANOUT		
FD FV	FLOOR DRAIN FLUSH VALVE	x	FIXTURE TAG (LEVEL BELOW FIXTURE)
'	FOOT, FEET		
(F)	FUTURE	<pre></pre>	PLUMBING EQUIPMENT IDENTIFICATION
GPH	GALLONS PER HOUR		
GPM GD	GALLONS PER MINUTE GARBAGE DISPOSER, GARAGE DRAIN	Piping Fitting	<u>15</u>
HD	HEAD, HUB DRAIN		ACCESS PANEL
HP	HEAT PUMP, HORSE POWER, HOUSEKEEPING PAD	L]	ACCESS PANEL
HZ	HERTZ		
HW HWFU	HOT WATER HOT WATER FIXTURE UNIT		BLIND FLANGE
IN, "	INCHES		
INV	INVERT ELEVATION	7	САР
KW	KILOWATT		CAF
L MW	LAVATORY MAKE-UP WATER		
MAX	MAXIMUM	——Ф <u>сот</u> сот <u>с</u>	CLEANOUT TO GRADE
HG	MERCURY		
MIN	MINIMUM		CONCENTRIC REDUCER
MX MH	MIXING VALVE MOUNTING HEIGHT, MANHOLE		
(N)	NEW		
NOP	NORMALLY OPEN	<u>N</u>	ECCENTRIC REDUCER
N	NORTH		
N/A NIC	NOT APPLICABLE NOT IN CONTRACT	~	EXPANSION JOINT
NTS	NOT TO SCALE	x	
#	NUMBER		
NO.	NUMBER		FLEXIBLE CONNECTION
OFCI OFOI	OWNER FURNISHED, CONTRACTOR INSTALLED OWNER FURNISHED, OWNER INSTALLED		
PH	PHASE	Ф <u>FCO</u>	FLOOR CLEANOUT
PLBG	PLUMBING	100	
Р	PLUMBING, PUMP		
POC PSI	POINT OF CONNECTION POUNDS PER SQUARE INCH		FLOW DIRECTION
PD	PRESSURE DROP, PLUMBING DEMOLITION, PUMPED DISCHARGE		
QTY	QUANTITY	M	METER
(R)	RELOCATE / RELOCATED LOCATION	-	
RPM SAN	REVOLUTIONS PER MINUTE SANITARY		
SJ	SEISMIC JOINT	<u> </u> ې	PIPE DROP
SB	SERVICE BOX		
SHT	SHEET	o	PIPE RISE
SA SOV	SHOCK ARRESTOR SHUT OFF VALVE		
S, SK	SINK	Ŷ	
SF	SQUARE FEET	<u> </u>	PRESSURE GAUGE WITH COCK
SP	SUMP PUMP, STATIC PRESSURE		
TEMP T	TEMPERATURE TEMPERATURE, THERMOMETER	§	SHOCK ABSORBER / WATER HAMMER ARR
TP	TRAP PRIMER, TOTAL PRESSURE		
TYP	TYPICAL		
V			TEE DOWN ON PIPE
VFD VS	VARIABLE FREQUENCY DRIVE VENT STACK		
vs VTR	VENT STACK VENT THRU ROOF	o	TEE UP ON PIPE
WCO	WALL CLEANOUT		
W	WASTE	Ю	THERMOMETER
WS WC	WASTE STACK	<u> </u>	
WC WC	WATER COLUMN WATER COLUMN, WATER CLOSET		
WHA	WATER HAMMER ARRESTOR		UNION
WH	WATER HEATER, WALL HYDRANT		
WSFU W/	WATER SUPPLY FIXTURE UNIT WITH	WCO	WALL CLEANOUT

Piping Systems

------ COLD WATER PIPING

D CONDENSATE / INDIRECT DRAIN PIPING

----- HOT WATER PIPING

----- SANITARY VENT PIPING

SANITARY WASTE OR SOIL PIPING ABOVE GRADE OR FINISHED

SANITARY WASTE OR SOIL PIPING BELOW GRADE OR FINISHED

<u>Valves</u>

ARRESTOR


GENERAL PLUMBING NOTES

- A. CONDITIONS SHOWN ON PLANS RELATIVE TO THE WORK TO BE PERFORMED ARE BASED ON THE BEST INFORMATION AVAILABLE BUT ARE SUBJECT TO VERIFICATION. VERIFY LOCATIONS AND ELEVATIONS OF UTILITIES TO BE CROSSED OR CONNECTED. CORRECT DEFICIENCIES CAUSED BY FAILURE TO PERFORM SUCH VARIFICATIONS AT NO EXPENSE TO THE OWNER. IMMEDIATELY NOTIFY ARCHITECT AND ENGINEER OF CONDITION IN CONFLICT.
- B. LOCATE VALVES FOR SERVICE ACCESSIBILITY. VALVES INSTALLED ABOVE CEILING SHALL BE WITHIN 18" OF CEILING.
- C. COORDINATE INSTALLATION OF PIPING BELOW AND ABOVE GRADE WITH STRUCTURAL COMPONENTS AND OTHER SYSTEMS INSTALLATION.
- D. COORDINATE FIXTURES, EQUIPMENT, PIPE ROUGH-IN CONNECTION LOCATIONS AND DRAIN LOCATIONS WITH ARCHITECTURAL DRAWINGS.
- E. COORDINATE DEMOLITION, SAW-CUTTING, PATCHING, ETC. WITH GENERAL CONTRACTOR AND EXISTING FIELD CONDITIONS.
- F. CONTRACTOR SHALL VERIFY AND COORDINATE ALL EXISTING WASTE, VENT AND WATER PIPING TO REMAIN IN SERVICE.
 G. PROVIDE CLEANOUTS FOR SANITARY WASTE SYSTEMS WHERE SHOWN AND AS OTHERWISE REQUIRED BY CODE.




P0001 SYMBOL LIST AND GENERAL NOTES - PLUMBINGP0002 SCHEDULES - PLUMBINGP1400 FLOOR PLAN - UNDERGROUND - PLUMBING


P1400 FLOOR PLAN - UNDERGROUND - PLUMBING P1401 FLOOR PLAN - GROUND LEVEL - PLUMBING



	PLUMBING FIXTURE SCHEDULE													
			BASIS OF	- DESIGN			CON	NECTION						
SYMBOL	FIXTURE TYPE	DESCRIPTION	MFR	MODEL	ACCESSORIES	W	V	CW	HW	ELECTRICAL	COMMENTS			
L-1	LAVATORY	WALL HUNG, ADA COMPLIANT, VITREOUS CHINA, SINGLE-HOLE PUNCH, FRONT OVERFLOW	KOHLER	K-2007	DECK MOUNTED, MANUAL OPERATED METERED, TWO HOLE, 0.25 GPM; CHICAGO FAUCETS MODEL 802-VE2805-665CP, ASSE 1070 COMPLIANT MIXING VALVE, INTEGRAL CHECK VALVES, WATTS MODEL LFMMV (SET DISCHARGE TEMPERATURE AT 110 DEG).	1-1/2"	1-1/2"	1/2"	1/2"		MOUNT LAVATORY AT ADA COMPLI HEIGHT, SEE ARCHITECTURAL PLA FOR HEIGHT AND LOCATION. SEE SPECIFICATION SECTION 224000 FO FLOOR MOUNTED CARRIER, TRAP COVERS, SUPPLY STOPS AND ADDITIONAL ACCESSORIES			
S-1	SINK	DROP-IN, SINGLE BOWL, 18 GAUGE STAINLESS STEEL, 22-INCHES X 22-INCHES X 6-1/2-INCHES DEEP, 27-INCH MINIMUM CABINET SIZE, 3-HOLE PUNCH, BARRIER FREE	ELKAY	LRAD222265	DECK MOUNTED FAUCET, 9.5-INCH RIGID/SWING GOOSENECK, 4" WRISTBLADE HANDLES, 4-INCH FIXED CENTERS, 1.5 GPM AERATED FLOW RATE; CHICAGO FAUCETS MODEL 895-317ABCP	2"	1-1/2"	1/2"	1/2"		SEE SPECIFICATION SECTION 2240 FOR SUPPLY STOPS AND ADDITION ACCESSORIES.			
WC-1	WATER CLOSET	WALL HUNG, 1.28 GPF MANUAL FLUSHOMETER, VITREOUS CHINA, TOP SPUD, ADA MOUNTING HEIGHT	KOHLER	K-84325-L	FLUSH VALVE - MANUAL OPERATED FLUSH VALVE 1.28 GPF, POLISHED CHROME FINISH, TOP SPUD; SLOAN ROYAL 111-1.28; SEAT - ELONGATED, PLASTIC, SELF-SUSTAINING CHECK HINGES WITH NON-CORRODING STAINLESS STEEL POSTS; BEMIS MODEL 1955SSCT	4"	2"	1-1/4"			MOUNT WATER CLOSET AT ADA HEIGHT, SEE ARCHITECTURAL PLA FOR HEIGHT AND LOCATION. SEE SPECIFICATION SECTION 224000 FO FLOOR MOUNTED CARRIER AND ADDITIONAL ACCESSORIES.			

	ELECTRIC WATER HEATER SCHEDULE - TANKLESS													
			BASIS O	F DESIGN	CA	PACITY		ELEC	TRICAL					
SYMBOL	EQUIPMENT TYPE	LOCATION / SERVING	MFR	MODEL	FLOW RATE (GPM)	TEMPERATURE RISE (DEG F)	VOLTS	PH	KW	AMPS	COMMENTS			
EWH-1	TANK LESS WATER HEATER	RESTROOM / BOTH L-1	EEMAX	SPEX4277T ML	.25 GPM	56 DEGREE RISE	277	1	4.1	15	TURNS ON AT 0.2 GPM			
EWH-2	TANK LESS WATER HEATER	UNDER COUNTER / S-1	EEMAX	SPEX100T ML	.2 - 1 GPM	68 DEGREE RISE	277	1	10	36	TURNS ON AT 0.2 GPM			
NOTES:														





_____ _____ _____ _____ _____ (E) 4 "SAN — 🔨 _____ *Q*___

K

 \frown

6


(7B)

 \checkmark


8


9

0' 4' 8' 16' 1/8" = 1'-0"



2 FLOOR PLAN - SECTOR A - PLUMBING









 \frown

6



0' 4' 8' 16' 1/8" = 1'-0"

2 FLOOR PLAN - SECTOR A - PLUMBING



		MECHANICAL SYMBOL LIST
TE: This is a	standard symbol list and not all items listed may be use	d.
Abbreviat	<u>ions</u>	Control Symbols
AFF	ABOVE FINISHED FLOOR	\sim
AD A/C	ACCESS DOOR AIR CONDITION(ED)	T AIR TEMPERATURE SENSOR
A/C AHU	AIR HANDLING UNIT	Democra
BDD	BACKDRAFT DAMPER	Dampers
BHP	BRAKE HORSEPOWER	
CD	CEILING DIFFUSER	
CL COP	CENTERLINE COEFFICIENT OF PERFORMANCE	Diffusers and Grilles
COP CONT.	COEFFICIENT OF PERFORMANCE	
CFM	CUBIC FEET PER MINUTE	12×12 CD-1 DIFFUSER OR GRILLE IDENTIFICATION
DB	DECIBEL	
DIA	DIAMETER	
DB EFF	DRY BULB EFFICIENT	SLOT DIFFUSER
ELECT	ELECTRICAL	
EL	ELEVATION	🖂 🚫 EXHAUST AIR
EAT	ENTERING AIR TEMPERATURE	
EXH	EXHAUST	
EF (E)	EXHAUST FAN EXISTING	RETURN AIR
(E) F	FAHRENHEIT	
FC	FAN COIL	
FT	FEET	
FPM	FEET PER MINUTE	Ductwork Fittings
FPI	FINS PER INCH	<u>Ductwork Fittings</u>
FC FLA	FLEXIBLE CONNECTOR FULL LOAD AMPS	ACOUSTICALLY LINED DUCT (SIZES SHOWN ARE NET INSIDE)
HTG	HEATING	
HP	HORSEPOWER	
IN	INCHES	
KW	KILOWATT	
LAT		
MAX MIN	MAXIMUM MINIMUM	CONCENTRIC TRANSITION, RECTANGULAR OR ROUND
MA	MIXED AIR	
MD	MOTORIZED DAMPER	ECCENTRIC TRANSITION, RECTANGULAR OR ROUND
NC	NOISE CRITERIA	
N/A	NOT APPLICABLE	
NIC		FLEX DUCT
NTS NO.	NOT TO SCALE NUMBER	
OC	ON CENTER	
OBD	OPPOSED BLADE DAMPER	
OA	OUTSIDE AIR	
PH	PHASE	C RECTANGULAR DUCT DROP
LBS.	POUNDS	
QTY RH	QUANTITY RELATIVE HUMIDITY	
кп (R)	RELOCATE/RELOCATED LOCATION	
RET	RETURN	
RA	RETURN AIR	TT TT RECTANGULAR MAIN WITH RECTANGULAR BRANCH
RPM	REVOLUTIONS PER MINUTE	
SEER	SEASONAL ENERGY EFFICIENCY RATING	
SF		THE RECTANGULAR MAIN WITH ROUND BRANCH
SP SA	STATIC PRESSURE SUPPLY AIR	
T, TEMP	TEMPERATURE	
MBH	THOUSAND BTU'S PER HOUR	RECTANGULAR OFFSET LESS THAN 15%%d
VAV	VARIABLE AIR VOLUME	
VEL	VELOCITY	RECTANGULAR OFFSET MORE THAN 15%%d
V	VOLT	
VD W	VOLUME DAMPER (HAND OPERATOR)	
W W/	WATT WITH	C ROUND DUCT DROP
W/O	WITHOUT	
		S ROUND DUCT RISER

<u>General</u>

X

(xx-x

 $\langle x \rangle$

A XXX

----- EXISTING WORK

30"Ø ROUND DUCT SIZING

------ NEW WORK


30X16

KEYED NOTE


POINT OF CONNECTION

RECTANGULAR DUCT SIZING

SECTION NUMBER AND SHEET LOCATION



					FAI	N SC	HED	ULE									
		BASIS OF	DESIGN								E	LECT	RICAL				
				-		AIR									APPROX.	MAX	
						FLOW	TSP	FAN	MAX	SOUND					DIMS	WT	
SYMBOL	AREA SERVED	MFR	MODEL	TYPE	DRIVE	(CFM)	(IN H2O)	RPM	RPM	(SONES)	VOLTS	PH	BHP	MHP	(LxWxH)	(LBS)	NOTES
CEF-1*	ADA RR	PANASONIC	FV-0511VF1	CEILING	DIRECT	80	0.25	1142	-	<1	120	1	-	9.4W	10x10x6	10	1, 2, 3
CEF-2*	ADA RR	PANASONIC	FV-0511VF1	CEILING	DIRECT	80	0.25	1142	-	<1	120	1	-	9.4W	10x10x6	10	1, 2, 3
NOTES:									•			•					
1)	PROVIDE WITH ECM SMART M	IOTOR TECHNOLOG	Y RATED FOR CONT	INUOUS OPERA	ATION.												
2)	PROVIDE WITH INTERLOCK T	O ROOM OCCUPANC	Y SENSOR. ACTIVA	TE FAN ON SIGI	NAL FROM R	оом осс	UPANCY S	ENSOR. PF		/IN TIME DE	LAY OF 5	MIN	JTES E	BEFORE	E DEACTIVAT	ING. COC	RDINATE WITH DIV 26.
3)*	COORDINATE FAN NUMBER W	VITH FACILITIES. DET	ERMINE NEXT NUM	ERICAL VALUE.	ADJUST TO	BE BE NE	XT CONSE	CUTIVE NU	JMBERS.								



SHEET METAL DUCT. -----

GENERAL MECHANICAL NOTES


- A. CONDITIONS SHOWN ON THE PLANS RELATIVE TO THE WORK TO BE PERFORMED ARE BASED ON THE BEST INFORMATION AVAILABLE BUT ARE SUBJECT TO VERIFICATION. VERIFY LOCATIONS AND ELEVATIONS OF UTILITIES. CORRECT DEFICIENCIES CAUSED BY FAILURE TO PERFORM SUCH VERIFICATIONS AT NO EXPENSE TO OWNER. IMMEDIATELY NOTIFY ARCHITECT OF CONDITION IN CONFLICT WITH THE PLANS.
- B. COORDINATE INSTALLATION OF DUCTWORK, PIPING, FIXTURES, EQUIPMENT, ETC. WITH ARCHITECTURAL, STRUCTURAL, MECHANICAL, ELECTRICAL AND FIRE PROTECTION SYSTEMS PRIOR TO INSTALLATION. C. COORDINATE EXACT LOCATION OF ALL CEILING GRILLES AND DIFFUSERS WITH ARCHITECTURAL REFLECTED CEILING PLAN, ARCHITECTURAL INTERIOR ELEVATIONS, LIGHTING, AND STRUCTURAL CONDITIONS. ARCHITECTURAL PLANS TO
- PROVIDE FINAL GRILLE AND DIFFUSER LOCATIONS IN THE EVENT OF A CONFLICT. D. ALL WORK PERFORMED AND MATERIAL SUPPLIED SHALL CONFORM TO ALL STATE AND LOCAL CODES AND ALL OTHER APPLICABLE LAWS AND STATE REGULATIONS INCLUDING APPLICABLE SEISMIC ZONE REQUIREMENTS.
- E. CONTRACTOR TO TEMPORARILY INSTALL 2" THICK 60% EFFICIENT FILTERS AT ALL RETURN AIR GRILLE LOCATIONS. FILTERS TO BE REMOVED AT CONCLUSION OF CONSTRUCTION.
- F. PAINT ALL DIFFUSERS, REGISTERS AND GRILLES PER ARCHITECTURAL INSTRUCTIONS. ANY GRILLES INSTALLED IN GYPSUM BOARD WALLS AND CEILINGS ARE TO BE FURNISHED WITH FACTORY MILL OR PRIMER FINISH, READY FOR PAINTING IN THE FIELD. G. DIFFUSER/GRILLE RUNOUTS ARE SAME SIZE AS DIFFUSER/GRILLE NECK SIZE UNLESS OTHERWISE NOTED ON PLANS.
- H. EQUIPMENT TO BE ACCESSIBLE FOR INSPECTION, SERVICE, REPAIR AND REPLACEMENT WITHOUT REMOVING PERMANENT CONSTRUCTION, OTHER EQUIPMENT, VENTING SYSTEMS, PIPING, OR DUCTS CONNECTED TO THE EQUIPMENT BEING SERVICED.
- I. MAINTAIN MINIMUM DISTANCE OF 3'-0" BETWEEN ALL EXHAUST OUTLETS AND DOORS/OPERABLE WINDOWS.
- J. PROVIDE ONE BALANCING DAMPER FOR EACH AIR INLET/ OUTLET SHOWN ON PLAN. WHERE DAMPER IS LOCATED ABOVE A HARD LID CEILING, PROVIDE REMOTE CABLE CONTROL FOR DAMPER. K. FOR ALL DUCT CONNECTIONS TO MECHANICAL EQUIPMENT, PROVIDE TRANSITION FROM DUCT SIZE SHOWN TO
- EQUIPMENT CONNECTION SIZE. L. ADJUST THROW OF ALL AIR DEVICES TO NOT INTERFERE WITH LIGHTING.
- M. INSTALL ALL EQUIPMENT SUCH THAT MANUFACTURER RECOMMENDED CLEARANCES ARE MAINTAINED.
- N. DETAILS APPLY WHETHER REFERENCED ON THE DRAWINGS OR NOT.
- O. INSTALL 1.5X RADIUS ELBOWS WHERE SPACE ALLOWS. OTHERWISE INSTALL MITERED ELBOWS WITH TURNING VANES CONSISTENT WITH SPECIFICATIONS.
- P. DUCTS, PIPING, AND EQUIPMENT TO BE INSTALLED AS HIGH AS POSSIBLE IN SPACES UNLESS OTHERWISE NOTED.
- Q. COORDINATE WITH ARCHITECTURAL AND STRUCTURAL DRAWINGS FOR WALL PENETRATIONS.
- R. SUPPORT EQUIPMENT, DUCTS, PIPING AS SPECIFIED AND AS SHOWN IN DETAILS. ENSURE EQUIPMENT WILL OPERATE WITHOUT OBJECTIONABLE VIBRATION AND NOISE.
- S. WHERE THE INSIDE OF DUCTS ARE VISIBLE FROM GRILLES OR DIFFUSERS, PAINT VISIBLE PORTION OF INSIDE OF DUCT FLAT BLACK.


COORDINATE FAN NUMBER WITH FACILITIES. DETERMINE NEXT NUMERICAL VALUE, ADJUST TO BE BE NEXT CONSECUTIVE NUMBERS.




M0001 SYMBOL LIST, GENERAL NOTES, DETAILS, & SCHEDULES - MECHANICAL

M1401 FLOOR PLAN - GROUND LEVEL - MECHANICAL









6

0' 4' 8' 16' 1/8" = 1'-0"

○ <u>SHEET KEYNOTES</u>

- 1. PROVIDE CONICAL CONNECTIONS TO BACK OF LOUVER PLENUM. PROVIDE OFFSET IN DUCTWORK AS REQUIRED TO ALIGN WITH OPENING ABOVE LEDGER AND BELOW STRUCTURAL BEAM. REFER TO ARCHITECTURAL LOUVER DETAIL FOR ADDITIONAL INFORMATION.
- 2. PROVIDE INSULATED, SHEET METAL PLENUM ON BACK OF LOUVER, FULL WIDTH AND HEIGHT OF LOUVER, APPROX. 95"Wx18"H. COORDINATE DEPTH OF PLENUM WITH LEDGER. REFER TO ARCHITECTURAL LOUVER DETAIL FOR ADDITIONAL INFORMATION.
- 3. ALIGN CEILING EXHAUST FAN IN CEILING WITH TOILET BELOW, CENTERLINE TO CENTERLINE. REFER TO ARCHITECTURAL RCP FOR FINAL LOCATION.
- 4. INTERLOCK FAN ON/OFF OPERATION WITH ROOM OCCUPANCY SENSOR. PROVIDE MIN TIME DELAY OF 5 MINUTES BEFORE DEACTIVATING FAN TO PREVENT SHORT CYCLING. PROVIDE RELAY, WIRING, AND ALL COMPONENTS REQUIRED FOR A COMPLETE INSTALLATION. COORDINATE WITH DIV 26 CONTRACTOR FOR INTEGRATION WITH OCCUPANCY SENSOR INSTALLATION.
- 5. RELOCATE EXISTING CEILING DIFFUSER TO NEXT AVAILABLE CEILING TILE, SOUTH OF NEW RESTROOMS. PROVIDE NEW FLEXIBLE DUCT AND RECONNECT TO OPERATE AS BEFORE.
- 6. RELOCATE EXISTING THERMOSTAT OUTSIDE OF NEW RESTROOMS AS INDICATED. RECONNECT TO OPERATE AS BEFORE.

6

 \frown -(7A)

 \checkmark

-**7**B

8

 \checkmark

 \frown

 \searrow


(13)

 \checkmark

-(11)

2 FLOOR PLAN - SECTOR A - MECHANICAL





NOTE: This is	a standard symbol list and not all items listed may be used.		
Abbreviat	ione	Connection	is / Equipment
AFC	ABOVE FINISHED CEILING	<u>connection</u>	
AFF	ABOVE FINISHED FLOOR	F	HEAVY DUTY FUSED DISCONNECT SWITCH
AFG			
ARF ANSI	ABOVE RAISED FLOOR AMERICAN NATIONAL STANDARDS INSTITUTE	Ø	MOTOR CONNECTION
AWG	AMERICAN WIRE GAUGE	\sim	
А	AMPERES, AMBER		
AV AHJ	AUDIO VISUAL AUTHORITY HAVING JURISDICTION	Ľ	NON-FUSED DISCONNECT SWITCH
AIC	AVAILABLE INTERRUPTING CAPACITY		
BAS	BUILDING AUTOMATION SYSTEM	Q	WALL-MOUNTED JUNCTION BOX
CA	CABLE	-	
CAT CLG	CATEGORY CEILING	<u>General</u>	
CB	CIRCUIT BREAKER	(\mathbf{x})	
С	CONDUIT, CLOSE, CONTROL	$\left(\begin{array}{c} \hat{x} \end{array}\right)$	DETAIL NUMBER AND SHEET LOCATION
CFCI CFOI	CONTRACTOR FURNISHED CONTRACTOR INSTALLED CONTRACTOR FURNISHED OWNER INSTALLED	\bigcirc	
COORD	COORDINATE	$\langle xx-x \rangle$	EQUIPMENT IDENTIFICATION
CU	COPPER		
dB	DECIBEL		
(X) DTL	DEMOLISH DETAIL	$\langle 1 \rangle$	KEYED NOTE
DIL	DIAMETER		
DIM	DIMENSION	•	POINT OF CONNECTION
DIV	DIVISION		
DN DWG	DOWN DRAWING		SECTION NUMBER AND SHEET LOCATION
EA	EACH	xxx x	SECTION NUMBER AND SHEET LOCATION
EMT	ELECTRICAL METALLIC TUBING		
ENT	ELECTRICAL NON-METALLIC TUBING	<u> </u>	- DEMOLISH
ESD EL	ELECTROSTATIC DISCHARGE ELEVATION		
E	EMERGENCY		– EXISTING WORK
EF	EXHAUST FAN		
(E)	EXISTING		
FMS FF	FACILITY MANAGEMENT SYSTEMS FINISH FLOOR		NEW WORK
FA	FIRE ALARM		
FACP	FIRE ALARM CONTROL PANEL	<u>Lighting</u>	
FMC	FLEXIBLE METAL CONDUIT		RECESSED 2' X 4' LUMINAIRE
FT FBO	FOOT, FEET FURNISHED BY OTHERS		
G, GND	GROUND		
GFCI	GROUND FAULT CIRCUIT INTERRUPTER	\bigcirc	RECESSED LUMINAIRE
GFI			
GFP GE	GROUND FAULT PROTECTION GROUNDING EQUALIZER	<u>Fo</u>	WALL MOUNTED 6" WIDE LUMINAIRE
HH	HANDHOLE		
HT	HEIGHT	<u>Miscellanec</u>	bus
HC ID	HORIZONTAL CROSS CONNECT IDENTIFICATION		BRANCH CIRCUIT WIRING. ARROW INDICATES HOME RUN TO
IN	INCH, INCHES	#10	PANEL WITH CIRCUITS AS NOTED. WIRE SIZE IS #12 AWG MINIMUM UNLESS NOTED OTHERWISE. SHORT TICK MARKS INDICATE PHASE
IEEE	INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS		CONDUCTORS. LONG TICK MARKS INDICATE NEUTRAL CONDUCTORS. A SINGLE CURVED TICK MARK INDICATES
IMC		B-27,29,31.	INSULATED GREEN GROUND CONDUCTOR. SECOND CURVED TICK
IG KV	ISOLATED GROUND KILOVOLT		MARK INDICATES "ISOLATED GROUND" (GREEN INSULATION WITH YELLOW STRIPE) CONDUCTOR.
KVA	KILOVOLT AMPERES		
KW	KILOWATT	\leq	BRANCH PANEL
LED	LIGHT EMITTING DIODE		
LNC LFMC	LIQUID TIGHT FLEXIBLE NONMETALLIC CONDUIT LIQUIDTIGHT FLEXIBLE METAL CONDUIT	\sim	
LV	LOW VOLTAGE	- <i>i</i> `	CIRCUIT BREAKER
MOCP	MAXIMUM OVERCURRENT PROTECTION		
MHz mA	MEGAHERTZ MILLIAMPERES	N	FLUSH MOUNT EQUIPMENT ENCLOSURE AS NOTED
MIN	MINIMUM		
MCA	MINIMUM CIRCUIT AMPS	6	FLUSH WALL MOUNTED BRANCH PANEL
MISC	MISCELLANEOUS		
M MCC	MOTOR MOTOR CONTROL CENTER	GB	
MT, MTD	MOTOR CONTROL CENTER MOUNT, MOUNTED	GB	GROUND BAR
MDU	MULTI-DWELLING UNIT		
NEC	NATIONAL ELECTRIC CODE	• lı	GROUNDING POINT
NESC NEMA	NATIONAL ELECTRIC SAFETY CODE NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION	- p.	
NEIMA	NEUTRAL		
(N)	NEW		MAIN DISTRIBUTION PANEL / SUB DISTRIBUTION PANEL
NC	NORMALLY CLOSED		
NO N/A	NORMALLY OPEN NOT APPLICABLE		SURFACE MOUNT EQUIPMENT ENCLOSURE AS NOTED
N.I.C.	NOT IN CONTRACT		
NTS	NOT TO SCALE		
	ON CENTER		
OSP OFCI	OUTSIDE PLANT OWNER FURNISHED, CONTRACTOR INSTALLED		
OFOI	OWNER FURNISHED, OWNER INSTALLED		
PNL	PANEL		
PH			
PVC PWR	POLY-VINYL-CHLORIDE POWER		
QTY	QUANTITY		
REF	REFERENCE		
(R)			
RFI REQD	REQUEST FOR INFORMATION REQUIRED		
REQD	RIGID METAL CONDUIT		
RM	ROOM		
OUT	SHEET		
SHT SIM	SIMILAR		

SPKR

STD

SPD

SWBD

TBB

TGB

TTB

TBD

XFMR

TVSS

TP

TYP

UG

UL UPS

UON

VFD VRFY

> V WP

WG

W

W/

W/O

SPEAKER

STANDARD

SWITCHBOARD

TO BE DETERMINED

TRANSITION POINT

TRANSFORMER

UNDERGROUND

VOLTS, VOLTAGE

WEATHERPROOF

WIRE GUARD

WIRE, WHITE

TYPICAL

VERIFY

WITH

WITHOUT

WAO WORK AREA OUTLET

SURGE PROTECTION DEVICE

TELEPHONE TERMINAL BOARD

UNDERWRITERS LABORATORIES

UNLESS OTHERWISE NOTED VARIABLE FREQUENCY DRIVE

UNINTERRUPTIBLE POWER SUPPLY

TELECOMMUNICATIONS BONDING BACKBONE

TELECOMMUNICATIONS GROUNDING BUS BAR


TRANSIENT VOLTAGE SURGE SUPPRESSOR

LECTRICAL SYMBOL LIST


 EXISTING CONDUIT ROUTED BELOW FLOOR / GRADE CONDUIT CONCEALED IN WALL OR CEILING SPACE CONDUIT ROUTED BELOW FLOOR / GRADE CONDUIT ROUTED BELOW FLOOR / GRADE CONDUIT ELLED DWN CONDUIT ELLED UP CONDUIT ELLED UP CONDUIT ELLED UP CONDUIT ELLED UP CONDUIT ELLED MULTIPLE LETTERS INDICATE MULTIPLE OCONDUIT ELLED WITH CONDUCTION SWItches and Receptacies DUPLEX RECEPTACLE (MULTIPLE LETTERS INDICATE MULTIPLE CONDUIT ELLED UP CONDUIT CONDUCTION SWItches and Receptacies DUPLEX RECEPTACLE (MULTIPLE LETTERS INDICATE MULTIPLE PEREDAIN MOUNTED FOUSSITIAT FORTECTED BY BREAKER IN PANEL GONDUS FAULT CIRCUIT INTERRUPTER H HOSPITAL FROTECTED BY BREAKER IN PANEL FOUSSITIAT FORTECTED BY DECUPANCY SENSOR RELAY S = SPLIT WIRED FURNITURE DROUCOPACY SENSOR RELAY S = SPLIT WIRED FURNITURE POWER CENTER DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR DOUBLE DUPLEX RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE SEE LETTER CODE DENOTES RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE SEE LETTER CODE DENOTES RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION SPLASING HALOWARD ON SERIAGINA TIME FAULTIPMENT DENSITY OF TACLES ON THE AND THE EQUIPMENT ENDISTICUE CONFIGURATION TRAGENT MUTH FROMENTO OFF. VILOWERCASE) - VACANCY CONTROL DESIGNATION VILOWERCASE) - VACANCY CONTROL DESIGN		EXISTING CONDUIT CONCEALED IN WALL OR CEILING SPACE
 CONDUIT CONCEALED IN WALL OR CELING SPACE CONDUIT ROUTED BELOW FLOOR / GRADE CONDUIT ELLED DOWN CONDUIT ELLED DOWN CONDUIT ELLED UP CONDUIT ELLED TOR B = CLOCK HANGER C = FLUSH CELING MOUNTED E = EMERGENCY F = CONTRE C = CONTRE D WITH CORD GRIPS. VERIEY PENDANT LENGTH T = NAMER RESISTANT COVER C = PENDANT MOUNTED BY OCCUPANCY SENSOR RELAY R = SUSTONED SECONTINUOUS USE COVER, GECI PROTECTED, WITH WEATHER RECEPTACLE, FLUSH FLOOR D OUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX R = COUPNENT ELECTRICAL CONNECTION SINGLE RECEPTACLE SEE LETTER CODE DENOTES SINGLE RECEPTACLE SEE LETTER CODE DENOTES R = COUPNENT ELECTRICAL CONNECTION SPECIAL PURPOSE RECEPTACLE LETTER CODE DENOTES R = COUPNENT ENDERATION TORING THE		EXISTING CONDULT CONCEALED IN WALL OR CEILING SPACE
 CONDUIT ROUTED BELOW FLOOR / GRADE CONDUIT ELLED DOWN CONDUIT ELLED UP CONDUIT REPEARCH (MULTIPLE LETTERS INDICATE MULTIPLE OPTIONS) A = ABOVE COUNTER B = CLOCK HANSER C = FURRERENCY F = ARC FAULT PROTOCTED BY BREAKER IN PANEL C = FURRERENCY F = ARC FAULT PROTOCTED BY BREAKER IN PANEL H = OOPTICAL GRADE K = OHLD RESISTANT COVER H = OOPTICAL GRADE K = OHLD RESISTANT COVER K = OHLD RESISTANT COVER K = OHLD RESISTANT COVER F = PROMANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LENGTH RT = HALF SWITCHED BY OCCUPANCY SENSOR RELAY S = FULR WITCHED BY OCCUPANCY SENSOR RELAY S = SPILT WIRED T = VERTISID W = WEATHERREDISTANT RECEPTACLE F URNITURE POWER CENTER DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR SINGLE RECEPTACLE SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE SEE LETTER CODE DENOTES RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE SEE LETTER CODE DENOTES RECEPTACLE CONFIGURATION TWIST-LOCK RECEPTACLE XXXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE XXXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE COURDING SERGEPTACLE LETTER CODE DENOTES RECEPTACLE CONFIGURATION TWIST-LOCK RECEPTACLE XXXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE YULTYRONGUNG SONDE SENSOR REPARTERN HUNDRING DOCLUPANCY SENSOR P = PASISING W		EXISTING CONDUIT ROUTED BELOW FLOOR / GRADE
 CONDUIT ELLED DOWN CONDUIT ELLED UP CONDUITWIRING CONTINUATION Switches and Receptacles DUPLEX RECEPTACLE (MULTIPLE LETTERS INDICATE MULTIPLE OPTIONS) A - 860VE COUNTER B - CLOCK HANGER C - FLUSH CELING MOUNTED E - ELING MOUNTED E - ELING MOUNTED E - ELING ACUTATION TO SPECAKER IN PANEL C - FLUSH CELING MOUNTED E - REFREENCY C - FLUSH CELING MOUNTED E - ARD RANDER MOUNTED C - FLUSH CELING MOUNTED E - ARD RANDE MOUNTED WITH CORD GRIPS. VERIFY PENDANT LENGTH R - AND RANDE MOUNTED WITH CORD GRIPS. VERIFY PENDANT LENGTH R - HALP SWITCHED BY OCCUPANCY SENSOR RELAY S - SPLITY WIRED T - TAMFER RESISTANT SHUTTERED RECEPTACLE W - WEATHERRED FOR CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHERRED FOR CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHERRED FOR CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHERRED FOR OPTIONS DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR DOUBLE DUPLEX RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE SEE LETTER CODE LIST AT DUPLEX RECEPTACLE CONFIGURATION TWIST-LOCK RECEPTACLE XXXXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE XXXR = NEMA CONFIGURATION TWIS		CONDUIT CONCEALED IN WALL OR CEILING SPACE
 CONDUIT ELLED UP CONDUITWIRING CONTINUATION SWIChes and Receptacle (MULTIPLE LETTERS INDICATE MULTIPLE OPTIONS) A = ABOVE COUNTER B = CLOCK HANGER C = FLUSH CELLING MOUNTED E = KIERGENCY F = LIGENEENCY F = LIGENEENCY F = CONTROL GRADE C = FLUSH CELLING MOUNTED F = KIERGENCY F = CONTROL CETED BY REAKER IN PANEL G = GROUND FAULT CIRCUIT INTERRUPTER H = HOSPITAL GRADE K = COLLID GROUND P = PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LENGTH R = HALF SWITCHED BY OCCUPANCY SENSOR RELAY S = SPLIT WIRED T = TAMFER RESISTANT COVER D = PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LENGTH R = HALF SWITCHED BY OCCUPANCY SENSOR RELAY S = SPLIT WIRED T = TAMFER RESISTANT SHUTTERED RECEPTACLE U = USB PORTIS) C = FURNITURE POWER CENTER D OUBLE DUPLEX RECEPTACLE, FLUSH FLOOR D = DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR D = DOUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS C = EQUIPMENT ELECTRICAL CONNECTION SPECIAL PURPOS RECEPTACLE LETTER CODE DENOTES RECEPTACLE FOR OPTIONS C = EQUIPMENT ELECTRICAL CONNECTION SPECIAL PURPOS RECEPTACLE LETTER CODE DENOTES RECEPTACLE FOR OPTIONS C = CONFIGURATION STINATION STUDIENT BLOER RECEPTACLE P = PENDANT MOUNT WITH CODE GRIPS. VERIFY PENDANT LENGTH X = COORDINATE RECEPTACLE LETTER CODE DENOTES RECEPTACLE FOR OPTIONS C = CUUPMENT ELECTRICAL CONNECTION SPECIAL PURPOSITION STINATION TIMETORY PENDANT LENGTH X = COORDINATE RECEPTACLE CONFIGURATION WITH EQUIPMENT BEING SUPPLIED CELLING MOUNTED OCCUPANCY SENSOR P = PASSIVE INFRARED WITH WEATHER OPTIONS C = D = DUALE ALLY PASSIVE INFRARED WITH MUED OCCUPANCY SENSOR P = PASSIVE INFRARED WITH INTEGRAL "OFF" SUTCHES D = PASSIVE INFRARED WITH INTEGRAL "OFF" SUTCHES D = PASSIVE INFRARED WITH INTEGRAL DESIGNATION WALL MOUNTED OCCUPANCY SENSOR P = PASSIVE INFRARED WITH INTEGRAL DESIGNATION SINCLE FOLE SWITCH 1 = DULALELY PASSIVE INFRARED WITH INTEGRAL DESIGNATION WALL MOUNTED OCCUPANCY SENSORSINTER D = PASSIVE INFRARED WITH I		CONDUIT ROUTED BELOW FLOOR / GRADE
 CONDUTIVIEND CONTINUATION Switches and Recoptacles DUPLEX RECEPTACLE (MULTIPLE LETTERS INDICATE MULTIPLE OPTIONS) A - RADVE COUNTER B - CLOCK HARGER C - FLUSH CARLIGER C - FLUSH CARLIER C - PERLAND GROUNTED WITH CORD GRIPS, VERIFY PENDANT LENGTH R - PARLY SWITCHED BY OCCUPANCY SENSOR RELAY R - PERLY SWITCHED BY OCCUPANCY SENSOR RELAY R - S - FULLY SWITCHED BY OCCUPANCY SENSOR RELAY R - S - FULLY SWITCHED BY OCCUPANCY SENSOR RELAY R - S - S - FULLY SWITCHED BY OCCUPANCY SENSOR RELAY R - S - S - S - S - S - S - S - S - S -	•	CONDUIT ELLED DOWN
Switches and Receptacles DUPLEX RECEPTACLE (MULTIPLE LETTERS INDICATE MULTIPLE OPTIONS) A 480VE COUNTER B = CLOCK HANGER C = FLUSH CEILING MOUNTED E = ENERGENCY F = ARC FAULT PROTECTED BY BREAKER IN PANEL G = GROUND FAULT CIRCUIT INTERRUPTER H = HOSPITAL GRADE K = CHILD RESISTANT COVER L = ISOLATED GROUND P = PENDANT MOUNTED WITH CORD GRIPS, VERIFY PENDANT LENGTH R1 = HALF SWITCHED BY OCCUPANCY SENSOR RELAY R2 = FULIT SWITCHED BY OCCUPANCY SENSOR RELAY R3 = SPLIT WIRED T TAMPER RESISTANT SHUTTERED RECEPTACLE U = USB PORT(S) W = WEATHERPROOF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHERPROOF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHER RESISTANT RECEPTACLE I = DOUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS I = COUPMENT ELECTRICAL CONNECTION SINGLE RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS I = COUPMENT ELECTRICAL CONNECTION SPECETACLE CONFIGURATION TWIST-LOCK RECEPTACLE I = COUPMART ELECTRICAL CONNECTION SECEPTACLE CONFIGURATION TWIST-LOCK RECEPTACLE I = DUAL RELAY PASSIVE INFRARED I = DUAL RELAY PASSIVE INFRARED I	0	CONDUIT ELLED UP
DUPLEX RECEPTACLE (MULTIPLE LETTERS INDICATE MULTIPLE OPTIONS) A - ABOYE COUNTER B - CLOCK HANGER C - CROWN FAILT CROWTED E - EMERGENCY F - ARC FAULT PROTECTED BY BREAKER IN PANEL G - GROWND FAULT CROWTINTERRUPTER H - HOSPITAL GRADE C - CROWND FAULT COULT INTERRUPTER H - HOSPITAL GRADE C - CROWND FAULT COULT INTERRUPTER H - HALF SWITCHED BY OCCUPANCY SENSOR RELAY S - SPLIT WIRED T - TAMPER RESISTANT SHUTTERED RECEPTACLE U - US BY DORT(S) W = WEATHERPROF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHER-RESISTANT RECEPTACLE DUBLE DUPLEX RECEPTACLE, FLUSH FLOOR W = WEATHERPROF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHER-RESISTANT RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS W SINGLE RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS W SINGLE RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS C SINGLE RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE CONFIGURATION TWIST-LOCK RECEPTACLE <	{	CONDUIT/WIRING CONTINUATION
OPTIONS) A 480VE COUNTER B = CLOCK HANGER C = CLUSH CELLING MOUNTED E = EMERGENCY F ARC FAULT PROTECTED BY BREAKER IN PANEL G = CROUND FAULT CIRCUIT INTERRUPTER H + 069THAL GRADE K = CHILD RESISTANT COVER L = ISOLATED GROUND P = PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LENGTH HILLY SWITCHED BY OCCUPANCY SENSOR RELAY R2 = FULLY SWITCHED BY OCCUPANCY SENSOR RELAY R3 = SPLIT WIRED T = TAMPRE RESISTANT SHUTTERED RECEPTACLE W = WEATHERPROF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHER-RESISTANT RECEPTACLE W = WEATHERPROF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHER-RESISTANT RECEPTACLE DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR DOUBLE DUPLEX RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS Image: RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS Image: REMAXENCIDANT TWIST-LOCK RECEPTACLE Image: REMAXENCIDATION TWIST-LOCK RECEPTACLE Image: REMAXENDING KAXXR = NEMA CONFIGURATION TWIST	Switches and	Receptacles
 A = ABOVE COUNTER B = CLOCK HANGER C = FLUSH CELLING MOUNTED E = EMERGENCY F = ARC FAULT PROTECTED BY BREAKER IN PANEL G = GROUND FAULT CIRCUIT INTERRUPTER H = HOSPITAL GRADE K = CHILD RESISTANT COVER L = ISOLATED GROUND P = PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LENGTH R = HALF SWITCHED BY OCCUPANCY SENSOR RELAY R = FULLY SWITCHED BY OCCUPANCY SENSOR RELAY R = FULLY SWITCHED BY OCCUPANCY SENSOR RELAY S = SPLILT WIRED T = TAMPER RESISTANT SHUTTERED RECEPTACLE U = USB PORT(S) W = WEATHER/RESISTANT RECEPTACLE FURNITURE POWER CENTER DOUBLE DUPLEX RECEPTACLE. FLUSH FLOOR DOUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION SPECIAL PURPOSE RECEPTACLE. LETTER CODE DENOTES RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION SPECIAL PURPOSE RECEPTACLE. LETTER CODE DENOTES RECEPTACLE CONFIGURATION TWIST-LOCK RECEPTACLE LXXXR = NEMA CONFIGURATION TRAGHT BLADE RECEPTACLE XXXR = NEMA CONFIGURATION TRAGHT BLADE RECEPTACLE YXXR = NEMA CONFIGURATION TRAGHT BLADE RECEPTACLE YXXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE YXXR = NEMA CONFIGURATION TRAGHT BLADE RECEPTACLE YXXR = NEMA CONFIGURATION TRAGHT BLADE RECEPTACLE 		
 E = EMERGENCY F = ARC FAULT PROTECTED BY BREAKER IN PANEL G = GROUND FAULT CIRCUIT INTERRUPTER H = HOSPTAL GRADE K = CHILD RESISTANT COVER L = SOLATED GROUND P = PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LE ISOLATED GROUND P = PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LE ISOLATED GROUND P = PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LE ISOLATED GROUND P = PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LE ISOLATED GROUND P = PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LE US BY PORT (S) Y = FULLY SWITCHED BY OCCUPANCY SENSOR RELAY S = SPLIT WIRED T = TAMPER RESISTANT SHUTTERED RECEPTACLE U = USB PORT (S) W = WEATHERRRESISTANT RECEPTACLE FURNITURE POWER CENTER DOUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION SPECIAL PURPOSE RECEPTACLE LETTER CODE DENOTES RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION SPECIAL PURPOSE RECEPTACLE LETTER CODE DENOTES RECEPTACLE CONFIGURATION TWISTLOCK RECEPTACLE XXR = NEMA CONFIGURATION TWISTLOCK RECEPTACLE XXR = NEMA CONFIGURATION TWISTLOCK RECEPTACLE ENTRY NUTH CORD GRIPS. VERIFY PENDANT LENGTH X: COORDINATE RECEPTACLE CONFIGURATION WITH EQUIPMENT BEING SUPLIED CELLING MOUNTED OCCUPANCY SENSOR P = PASSIVE INFRARED WITH INTEGRAL OFF? SWITCH Y LOWERCASE) = VACANCY CONTROL DESIGNATION WALL MOUNTED OCCUPANCY SENSORS/WITCH S PASSIVE INFRARED WITH INTEGRAL OFF? SWITCH T RULZ RELAY PASSIVE INFRARED WITH TWO INTEGRAL OFF? WITCHES D = DUAL TECHNOLOGY D = DU		A = ABOVE COUNTER
 F = ÅRC FAÜLT PROTECTED BY BREAKER IN PANEL G = GROUND FAULT CIRCUIT INTERRUPTER H = HOSPITAL GRADE K = CHILD RESISTANT COVER L = ISOLATED GROUND P.= PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LENGTH RI = HAIL F SWITCHED BY OCCUPANCY SENSOR RELAY R2 = FULLY SWITCHED BY OCCUPANCY SENSOR RELAY R2 = FULLY SWITCHED BY OCCUPANCY SENSOR RELAY R2 = FULLY SWITCHED BY OCCUPANCY SENSOR RELAY S = SPLIT WIRED T = TAMPER RESISTANT SHUTTERED RECEPTACLE U = USB PORT(S) W = WEATHERPROOF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHERPROOF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHERPRESISTANT RECEPTACLE DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR DOUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS DOUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE. SEE LETTER CODE DENOTES RECEPTACLE CONFIGURATION SINGLE RECEPTACLE. LETTER CODE DENOTES RECEPTACLE CONFIGURATION TWIST-LOCK RECEPTACLE XXXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE XXXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE XXXR = NEMA CONFIGURATION TWISTALORY PENDANT LENGTH X = COORDINATE RECEPTACLE CONFIGURATION WITH EQUIPMENT BEING SUPLED CELUNG MOUNTED OCCUPANCY SENSOR P = PROSIVE INFRARED DIJULATECHNOLOGY U = ULTRASONIC, MALWAY PATTERN v (LOWERCASE) = VACANCY CONTROL DESIGNATION v LURASONIC, MALWAY PATTERN v DUAL TECHNARED WITH INTEGRAL OVFF' SWITCH THRUE X WAY SWITCH THAUE X WOW		C = FLUSH CEILING MOUNTED
 H = HOSPITAL GRADE K = CHILD RESISTANT COVER L = ISOLATED GROUND P = PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LENGTH R1 = HAI F SWITCHED BY OCCUPANCY SENSOR RELAY R2 = FULLY SWITCHED BY OCCUPANCY SENSOR RELAY R2 = FULLY SWITCHED BY OCCUPANCY SENSOR RELAY S = SPLIT WIRED T = TAMPER RESISTANT SHUTTERED RECEPTACLE U = USB PORT(S) w = WEATHERPROOF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHER-RESISTANT RECEPTACLE FURNITURE POWER CENTER DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR DOUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE. SEE LETTER CODE DENOTES RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION SPECIAL PURPOSE RECEPTACLE. LETTER CODE DENOTES RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION SPECIAL PURPOSE RECEPTACLE. LETTER CODE DENOTES RECEPTACLE CONFIGURATION TWIST-LOCK RECEPTACLE XXXR = NEMA CONFIGURATION TRIGHT BLADE RECEPTACLE XXXR = NEMA CONFIGURATION TRIGHT BLADE RECEPTACLE XXXR = NEMA CONFIGURATION TRIGHTB ADDE RECEPTACLE XXXR = NEMA CONFIGURATION TRIGHTB NADE RECEPTACLE YAXR = NEMA CONFIGURATION TRIGHTB ADDE RECEPTACLE XXXR = NEMA CONFIGURATION TRIGHTB NADE RECEPTACLE YAXR = NEMA CONFIGURATION TRIGHTB ADDE RECEPTACLE YAXR = NEMA CONFIGURATION TRIGHTS ADDE RECEPTACLE YALMOVERCASE) = VACANCY CONTROL DESIGNATION WITH EQUIPMENT BEING SUPPLIED CELING MOUNTED OCCUPANCY SENSOR/SWITCH YE PASSIVE INFRARED WITH INTEGRAL DIMMER TO OFF. Y (LOWERCASE) = VACANCY CONTROL DESIGNATION WICHARCENCH YALRE-WAY SWITCH YALRE-W		F = ARC FAULT PROTECTED BY BREAKER IN PANEL
 L = ISOLATED GROUND P = PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT LENGTH R1 = HALF SWITCHED BY OCCUPANCY SENSOR RELAY R2 = FULLY SWITCHED BY OCCUPANCY SENSOR RELAY S = SPLIT WIRED T = TAMPER RESISTANT SHUTTERED RECEPTACLE U = USB PORT(S) W = WEATHERPROOF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHER-RESISTANT RECEPTACLE U = USB PORT(S) W = WEATHERPROOF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHER-RESISTANT RECEPTACLE DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR DOUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS DOUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE. SEE LETTER CODE DENOTES RECEPTACLE FOR OPTIONS SECIAL PURPOSE RECEPTACLE. LETTER CODE DENOTES RECEPTACLE FOR OPTIONS SPECIAL PURPOSE RECEPTACLE. LETTER CODE DENOTES RECEPTACLE CONFIGURATION TWIST-LOCK RECEPTACLE X-XXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE Y = PENDANT MOUNT WITH CORD GRIPS. VERIFY PENDANT LENGTH X = CORDINATE RECEPTACLE CONFIGURATION WITH EQUIPMENT BEING SUPPLIED CEILING MOUNTED OCCUPANCY SENSOR/SWITCH X = CORDINATE RECEPTACLE CONFIGURATION WITH EQUIPMENT BEING SUPLIED CEILING MOUNTED OCCUPANCY SENSOR/SWITCH Y LOWERCASE) = VACANCY CONTROL DESIGNATION WALL MOUNTED OCCUPANCY SENSOR/SWITCH Y DAUL RELAY PASSIVE INFRARED WITH INTEGRAL OFF' SWITCH T DUAL RELAY PASSIVE INFRARED WITH INTEGRAL OFF' SWITCH T DUAL RELAY PASSIVE INFRARED WITH INTEGRAL OFF' SWITCH T ANSIVE INFRA		H = HOSPITAL GRADE
LENGTH R1 = HALF SWITCHED BY OCCUPANCY SENSOR RELAY R1 = HALF SWITCHED BY OCCUPANCY SENSOR RELAY S = SPLIT WIRED T = TAMPER RESISTANT SHUTTERED RECEPTACLE U = USB PORT(S) W = WEATHERPROOF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHER-RESISTANT RECEPTACLE Image: Double Duplex Receptacle, FLUSH FLOOR Image: Double Duplex RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS Image: Double Duplex RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS Image: Double Duplex RECEPTACLE. LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS Image: Double Duplex RECEPTACLE. LETTER CODE DENOTES RECEPTACLE CONFIGURATION TWIST-LOCK RECEPTACLE Image: Receptacle Configuration Twist-Lock RECEPTACLE Image: RECEPTACLE CONFIGURATION TRAIGHT BLADE RECEPTACLE Image: RECEPTACLE CONFIGURATION WITH EQUIPMENT BEING SUPPLIED Image: RECEPTACL	Φ	
 FALE SWITCHED BY OCCUPANCY SENSOR RELAY R2 = FPLIT WIRED T = TAMPER RESISTANT SHUTTERED RECEPTACLE U = USB PORT(S) W = WEATHERPROOF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHER-RESISTANT RECEPTACLE FURNITURE POWER CENTER DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR DOUBLE DUPLEX RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION EQUIPMENT ELECTRICAL CONNECTION EQUIPMENT ELECTRICAL CONNECTION UX-XXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE P = PENDANT MOUNT WITH CORD GRIPS. VERIFY PENDANT LENGTH X = COORDINATE RECEPTACLE CONFIGURATION WITH EQUIPMENT BEING SUPPLIED CELLING MOUNTED OCCUPANCY SENSOR P = PASSIVE INFRARED D = DUAL TECHNOLOGY U = ULTRASONIC, 360 DEG RANGE H = ULTRASONIC, MALIWAY PATTERN V (LOWERCASE) = VACANCY CONTROL DESIGNATION WALL MOUNTED OCCUPANCY SENSOR P = PASSIVE INFRARED D = DUAL TECHNOLOGY U = ULTRASONIC, MALIWAY PATTERN V (LOWERCASE) = VACANCY CONTROL DESIGNATION WALL MOUNTED OCCUPANCY SENSORSWITCH S = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCH S = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCHES D = ASSIVE INFRARED WITH INTEGRAL "OFF" SWITCHES D = ASSIVE INFRARED WITH INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL OFF" SWITCH 3 = THRE-WAY SWITCH 4 = FOUR-WAY SWITCH 3 = THRE THAN DEE M = MANUAL MOTOR STARTER WITH THERMAL OVERLOAD P = SWITCH WITH PLOT LIGHT 3 = SENTRY SWITCH 	11/34/32	P = PENDANT MOUNTED WITH CORD GRIPS. VERIFY PENDANT
 S = SPLIT WIRED T = TAMPER RESISTANT SHUTTERED RECEPTACLE U = USB PORT(S) W = WEATHERPROOF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHER-RESISTANT RECEPTACLE FURNITURE POWER CENTER DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR DOUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION SPECIAL PURPOSE RECEPTACLE. LETTER CODE DENOTES RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION XXXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE XXXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE VXXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE XXXR = NEMA CONFIGURATION WIST-LOCK RECEPTACLE XXXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE XXXR = NEMA CONFIGURATION WIST-LOCK RECEPTACLE XXXR = NEMA CONFIGURATION WIST-LOCK RECEPTACLE YXXR = NEMA CONFIGURATION WIST-LOCK RECEPTACLE YXXR = NEMA CONFIGURATION WIST-LOCK RECEPTACLE YXXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE MALUARASONIC, HALLWAY PATTERN Y LOWERCASE) = VACANCY CONTROL DESIGNATION YULOWERCASE) = VACANCY CONTROL DESIGNATION YULOWERCASE) = VACANCY CONTROL DESIGNATION YULOWERCASE) = UMINAIRE CONTROL DESIGNATION YULCH SWITCH THREE-WAY SWITCH ETAN SPEED CONTROL		R1 = HALF SWITCHED BY OCCUPANCY SENSOR RELAY
U = USB PORT(S) W = WEATHERPROOF CONTINUOUS USE COVER, GFCI PROTECTED, WITH WEATHER-RESISTANT RECEPTACLE Image: Control of the state of the		S = SPLIT WIRED
WITH WEATHER-RESISTANT RECEPTACLE Image: Construct of the state of the		U = USB PORT(S)
 DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR DOUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE, SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION EQUIPMENT ELECTRICAL CONNECTION EQUIPMENT ELECTRICAL CONNECTION EQUIPMENT ELECTRICAL CONNECTION XXXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE P = PENDANT MOUNT WITH CORD GRIPS. VERIFY PENDANT LENGTH X = XXXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE P = PENDANT MOUNT WITH CORD GRIPS. VERIFY PENDANT LENGTH X = COORDINATE RECEPTACLE CONFIGURATION WITH EQUIPMENT BEING SUPPLIED CEILING MOUNTED OCCUPANCY SENSOR P = PASSIVE INFRARED D = DUAL TECHNOLOGY U = ULTRASONIC, 360 DEG RANGE H = DUAL RELAY PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL OFF" SWITCH S = PASSIVE INFRARED WITH INTEGRAL DIMMER TO OFF. V (LOWERCASE) = VACANCY CONTROL DESIGNATION WALL MOUNTED OCCUPANCY SENSOR/SWITCH S = DASSIVE INFRARED WITH INTEGRAL DIMMER TO OFF. V (LOWERCASE) = VACANCY CONTROL DESIGNATION WALL MOUNTED SENSOR INFRARED WITH INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL DIMMER TO OFF. V (LOWERCASE) = VACANCY CONTROL DESIGNATION SINGLE POLE SWITCH 3 = THREE-WAY SWITCH 4 = FOUR-WAY SWITCH 4 = FOUR-WAY SWITCH 5 = FAN SPEED CONTROL 5 K = KEY OPERATED SWITCH L = LIGHTED HANDLE M = MANUAL MOTOR STARTER WITH THERMAL OVERLOAD P = SWITCH WITH PILOT LIGHT S = SENTRY SWITCH 		
 DOUBLE DUPLEX RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION EQUIPMENT ELECTRICAL CONNECTION EQUIPMENT ELECTRICAL CONNECTION EQUIPMENT ELECTRICAL CONNECTION XXXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE X-XXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE X-XXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE Y LOUAL TECHNOLOGY Y = DUAL TECHNOLOGY Y = DUAL TECHNOLOGY Y (LOWERCASE) = VACANCY CONTROL DESIGNATION YALL MOUNTED OCCUPANCY SENSOR/SWITCH S = PASSIVE INFRARED WITH INTEGRAL DIMMER TO OFF. Y (LOWERCASE) = VACANCY CONTROL DESIGNATION Y DUAL RELAY PASSIVE INFRARED WITH TWO INTEGRAL "OFF" SWITCH S = TOUBLE POLE SWITCH S = FOUR-WAY SWITCH A THREE-WAY SWITCH A THREE WAY SWITCH A THRUE Y (LOWERCASE) = LUMINAIRE CONTROL DESIGNATION D DIMMER F = FAN SPEED CONTROL K = KEY OPERATED SWITCH LIGHTED HANDLE M = MANUAL MOTOR STARTER	\square	FURNITURE POWER CENTER
 RECEPTACLE FOR OPTIONS SINGLE RECEPTACLE. SEE LETTER CODE LIST AT DUPLEX RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION SPECIAL PURPOSE RECEPTACLE. LETTER CODE DENOTES RECEPTACLE CONFIGURATION LX-XXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE X-XXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE P = PENDANT MOUNT WITH CORD GRIPS. VERIFY PENDANT LENGTH X = COORDINATE RECEPTACLE CONFIGURATION WITH EQUIPMENT BEING SUPPLIED CEILING MOUNTED OCCUPANCY SENSOR P = PASSIVE INFRARED U = ULTRASONIC, 300 DEG RANGE H = ULTRASONIC, HALLWAY PATTERN v (LOWERCASE) = VACANCY CONTROL DESIGNATION WALL MOUNTED OCCUPANCY SENSOR/SWITCH S = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCH T = DUAL RELAY PASSIVE INFRARED WITH TWO INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL DIMMER TO OFF. v (LOWERCASE) = VACANCY CONTROL DESIGNATION SINGLE POLE SWITCH 2 = DOUBLE POLE SWITCH 3 = THREE-WAY SWITCH 4 = FOUR-WAY SWITCH 4 = FOUR-WAY SWITCH 4 = FOUR-WAY SWITCH 5 = TAN SPEED CONTROL 5 = ANSPEED CONTROL 5 = SENTRY SWITCH C = SENTRY SWITCH C = SENTRY SWITCH C = SENTRY SWITCH C = SENTRY SWITCH 		DOUBLE DUPLEX RECEPTACLE, FLUSH FLOOR
 RECEPTACLE FOR OPTIONS EQUIPMENT ELECTRICAL CONNECTION SPECIAL PURPOSE RECEPTACLE. LETTER CODE DENOTES RECEPTACLE CONFIGURATION LX-XXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE X-XXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE X-XXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE X = PENDANT MOUNT WITH CORD GRIPS. VERIFY PENDANT LENGTH X = COORDINATE RECEPTACLE CONFIGURATION WITH EQUIPMENT BEING SUPPLIED CEILING MOUNTED OCCUPANCY SENSOR P = PASSIVE INFRARED D = DUAL TECHNOLOGY U = ULTRASONIC, 360 DEG RANGE H = ULTRASONIC, HALLWAY PATTERN v (LOWERCASE) = VACANCY CONTROL DESIGNATION WALL MOUNTED OCCUPANCY SENSOR/SWITCH S = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCH S = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL DIMMER TO OFF. v (LOWERCASE) = VACANCY CONTROL DESIGNATION SINGLE POLE SWITCH S = THREE-WAY SWITCH A = FOUR-WAY SWITCH A THRE 2. (OWERCASE) = LUMINAIRE CONTROL DESIGNATION D = DIMMER F = FAN SPEED CONTROL K = KEY OPERATED SWITCH K = KEY OPERATED SWITCH K = KEY OPERATED SWITCH L = LIGHTED HANDLE M = MANUAL MOTOR STARTER WITH THERMAL OVERLOAD P = SWITCH WITH PILOT LIGHT S = SENTRY SWITCH S = SENTRY SWITCH 	#	
 SPECIAL PURPOSE RECEPTACLE. LETTER CODE DENOTES RECEPTACLE CONFIGURATION LX-XXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE X-XXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE P = PENDANT MOUNT WITH CORD GRIPS. VERIFY PENDANT LENGTH X = COORDINATE RECEPTACLE CONFIGURATION WITH EQUIPMENT BEING SUPPLIED CEILING MOUNTED OCCUPANCY SENSOR P = PASSIVE INFRARED D = DUAL TECHNOLOGY U = ULTRASONIC, 360 DEG RANGE H = ULTRASONIC, 360 DEG RANGE H = ULTRASONIC, HALLWAY PATTERN v (LOWERCASE) = VACANCY CONTROL DESIGNATION WALL MOUNTED OCCUPANCY SENSOR/SWITCH S = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCH T = DUAL RELAY PASSIVE INFRARED WITH TWO INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL DIMMER TO OFF. v (LOWERCASE) = VACANCY CONTROL DESIGNATION SINGLE POLE SWITCH 2 = DOUBLE POLE SWITCH 3 = THREE-WAY SWITCH 4 = FOUR-WAY SWITCH 4 = FOUR-WAY SWITCH 3 THRU z (LOWERCASE) = LUMINAIRE CONTROL DESIGNATION D = DIMMER F = FAN SPEED CONTROL \$ K = KEY OPERATED SWITCH L = LIGHTED HANDLE M = MANUAL MOTOR STARTER WITH THERMAL OVERLOAD P = SWITCH WITH PILOT LIGHT S = SENTRY SWITCH 	Φ	
 RECEPTACLE CONFIGURATION LX-XXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE X-XXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE P = PENDANT MOUNT WITH CORD GRIPS. VERIFY PENDANT LENGTH X = COORDINATE RECEPTACLE CONFIGURATION WITH EQUIPMENT BEING SUPPLIED CEILING MOUNTED OCCUPANCY SENSOR P = PASSIVE INFRARED D = DUAL TECHNOLOGY U = ULTRASONIC, 360 DEG RANGE H = ULTRASONIC, 360 DEG RANGE H = ULTRASONIC, HALLWAY PATTERN v (LOWERCASE) = VACANCY CONTROL DESIGNATION WALL MOUNTED OCCUPANCY SENSOR/SWITCH S = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCH T = DUAL RELAY PASSIVE INFRARED WITH TWO INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL DIMMER TO OFF. v (LOWERCASE) = VACANCY CONTROL DESIGNATION SINGLE POLE SWITCH 3 = THREE-WAY SWITCH 4 = FOUR-WAY SWITCH 5 K = KEY OPERATED SWITCH L = LIGHTED CONTROL K = KEY OPERATED SWITCH L = LIGHTED THANDLE M = MANUAL MOTOR STARTER WITH THERMAL OVERLOAD P = SWITCH WITH PILOT LIGHT S = SENTRY SWITCH 	۲	EQUIPMENT ELECTRICAL CONNECTION
 CEILING MOUNTED OCCUPANCY SENSOR P = PASSIVE INFRARED D = DUAL TECHNOLOGY U = ULTRASONIC, 360 DEG RANGE H = ULTRASONIC, HALLWAY PATTERN v (LOWERCASE) = VACANCY CONTROL DESIGNATION WALL MOUNTED OCCUPANCY SENSOR/SWITCH S = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCH T = DUAL RELAY PASSIVE INFRARED WITH TWO INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL DIMMER TO OFF. v (LOWERCASE) = VACANCY CONTROL DESIGNATION SINGLE POLE SWITCH 2 = DOUBLE POLE SWITCH 3 = THREE-WAY SWITCH 4 = FOUR-WAY SWITCH a THREU Z (LOWERCASE) = LUMINAIRE CONTROL DESIGNATION D = DIMMER F = FAN SPEED CONTROL K K = KEY OPERATED SWITCH L = LIGHTED HANDLE M = MANUAL MOTOR STARTER WITH THERMAL OVERLOAD P = SWITCH WITH PILOT LIGHT S = SENTRY SWITCH 	٨	RECEPTACLE CONFIGURATION LX-XXR = NEMA CONFIGURATION TWIST-LOCK RECEPTACLE X-XXR = NEMA CONFIGURATION STRAIGHT BLADE RECEPTACLE P = PENDANT MOUNT WITH CORD GRIPS. VERIFY PENDANT LENGTH X = COORDINATE RECEPTACLE CONFIGURATION WITH EQUIPMENT
 In a strength of the standard strength of the str		CEILING MOUNTED OCCUPANCY SENSOR P = PASSIVE INFRARED D = DUAL TECHNOLOGY
S = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCH T = DUAL RELAY PASSIVE INFRARED WITH TWO INTEGRAL "OFF" SWITCHES D = PASSIVE INFRARED WITH INTEGRAL DIMMER TO OFF. v (LOWERCASE) = VACANCY CONTROL DESIGNATION SINGLE POLE SWITCH 2 = DOUBLE POLE SWITCH 3 = THREE-WAY SWITCH 4 = FOUR-WAY SWITCH a THRU z (LOWERCASE) = LUMINAIRE CONTROL DESIGNATION D = DIMMER F = FAN SPEED CONTROL K = KEY OPERATED SWITCH L = LIGHTED HANDLE M = MANUAL MOTOR STARTER WITH THERMAL OVERLOAD P = SWITCH WITH PILOT LIGHT S = SENTRY SWITCH	53	H = ULTRASONIC, HALLWAY PATTERN v (LOWERCASE) = VACANCY CONTROL DESIGNATION
 v (LOWERCASE) = VACANCY CONTROL DESIGNATION SINGLE POLE SWITCH 2 = DOUBLE POLE SWITCH 3 = THREE-WAY SWITCH 4 = FOUR-WAY SWITCH a THRU z (LOWERCASE) = LUMINAIRE CONTROL DESIGNATION D = DIMMER F = FAN SPEED CONTROL K = KEY OPERATED SWITCH L = LIGHTED HANDLE M = MANUAL MOTOR STARTER WITH THERMAL OVERLOAD P = SWITCH WITH PILOT LIGHT S = SENTRY SWITCH 	ssH	S = PASSIVE INFRARED WITH INTEGRAL "OFF" SWITCH T = DUAL RELAY PASSIVE INFRARED WITH TWO INTEGRAL "OFF" SWITCHES
 L = LIGHTED HANDLE M = MANUAL MOTOR STARTER WITH THERMAL OVERLOAD P = SWITCH WITH PILOT LIGHT S = SENTRY SWITCH 		<pre>v (LOWERCASE) = VACANCY CONTROL DESIGNATION SINGLE POLE SWITCH 2 = DOUBLE POLE SWITCH 3 = THREE-WAY SWITCH 4 = FOUR-WAY SWITCH a THRU z (LOWERCASE) = LUMINAIRE CONTROL DESIGNATION D = DIMMER F = FAN SPEED CONTROL</pre>
W = WEATHERPROOF SWITCH V = LOW VOLTAGE SWITCH	•	L = LIGHTED HANDLE M = MANUAL MOTOR STARTER WITH THERMAL OVERLOAD P = SWITCH WITH PILOT LIGHT S = SENTRY SWITCH T = INTERVAL TIMER W = WEATHERPROOF SWITCH V = LOW VOLTAGE SWITCH
Telecommunications RACEWAY ONLY DATA OUTLET. PROVIDE DOUBLE GANG BACK BOX	<u>i elecommuni</u>	

GENERAL ELECTRICAL NOTES

A. CONSULT ALL DRAWINGS AND SPECIFICATIONS IN THIS PROJECT AND BECOME FAMILIAR WITH ALL EQUIPMENT TO BE INSTALLED. COORDINATE ALL ASPECTS OF THE CONSTRUCTION WITH THE OTHER TRADES ON THE JOB TO ENSURE THAT ALL WORK AND MATERIALS REQUIRED PROVIDE A COMPLETE AND OPERATIONAL FACILITY ARE INCLUDED IN THE BID.



1 TYPICAL MOUNTING HEIGHTS



2 OUTLET LABELING

NO SCALE

NO SCALE




E0001 SYMBOL LIST AND GENERAL NOTES - ELECTRICAL

E1201 DEMOLITION PLANS - ELECTRICAL


- E1401 FLOOR PLAN GROUND LEVEL ELECTRICAL
- E1501 REFLECTED CEILING PLAN GROUND LEVEL LIGHTING


E6001 SCHEDULES - ELECTRICAL















○ <u>SHEET KEYNOTES</u>

- 1. REPLACE EXISTING DUPLEX RECEPTACLE WITH GFCI-TYPE RECEPTACLE. PROVIDE NEW COVERPLATE AND CIRCUIT LABEL.
- RECEPTACLES, (1) USB-A CONNECTION, AND (1) USB-C CONNECTION HORIZONTAL AND ABOVE COUNTER AS SHOWN IN DETAIL 2/A4102. EXTEND POWER FROM EXISTING CIRCUIT AT FLOOR BOX. CONTRACTOR SHALL COORDINATE THE LOCATIONS WITH ARCHITECTURAL DRAWINGS AND THE
- 3. RELOCATE EXISTING DEVICE. EXTEND CIRCUIT AS











GENERAL SHEET NOTES

A. CIRCUIT NEW LIGHTS IN RESTROOM TO EXISTING LIGHTING CIRCUIT IN THIS AREA ON NORMAL POWER. B. CIRCUIT NEW EXIT SIGN TO EXISTING LIGHTING CIRCUIT IN

THIS AREA. PROVIDE UNSWITCHED CIRCUIT FOR BATTERY CHARGING AND AUTOTRANSFER CIRCUITING.


○ SHEET KEYNOTES


1. OCCUPANCY SENSOR/SWITCH TO CONTROL LIGHTS AND FAN TOGETHER, COORDINATE WITH DIVISION 23.


2. RELOCATE LIGHT FIXTURE. EXTEND POWER AND CONTROL CIRCUIT AS NEEDED.

2 REFLECTED CEILING PLAN - SECTOR A - POWER

0'<u>4'</u>8'<u>1</u>6' 1/8" = 1'-0"









○ <u>SHEET KEYNOTES</u>

- 1. EXTEND EXISTING CIRCUIT IN ROOM TO NEW EXIT SIGNS. PROVIDE UNSWITCHED CIRCUIT FOR BATTERY CHARGING AND AUTOTRANSFER CIRCUITING.
- 2. PROVIDE NEW EMERGENCY BATTERY BACK WITH MINIMUM 1100 LUMENS FOR LUMINAIRE. PROVIDE UNSWITCHED CIRCUIT FOR BATTERY CHARGING AND AUTOTRANSFER CIRCUITING. PROVIDE TEST SWITCH MOUNTED FLUSH ON CEILING NEXT TO LUMINAIRE.
- 3. RELOCATE EXISTING LIGHT SWITCH AT THIS ENTRANCE TO NEW WALL. EXTEND CONTROL CIRCUIT AS NEEDED.

0'<u>4'</u>8'<u>1</u>6 1/8" = 1'-0"





1 THIS LUMINAIRE SCHEDULE IS NOT COMPLETE WITHOUT A COPY OF THE PROJECT MANUAL CONTAINING THE ELECTRICAL SPECIFICATIONS.

2 DIMMING CONTROL PROTOCOL (0-10VDC, LINE VOLTAGE, DALI, ETC.) COMPATIBLE WITH LIGHTING CONTROL SYSTEM AS SPECIFIED AND SHOWN ON DRAWINGS.

3 COORDINATE ALL CEILING TYPES WITH LUMINAIRE LOCATIONS PRIOR TO ORDERING LUMINAIRES. COORDINATE INSTALLATION WITH REFLECTED CEILING PLAN.

4 SPECIFIED MANUFACTURERS ARE APPROVED TO SUBMIT BID. INCLUSION DOES NOT RELIEVE MANUFACTURER FROM SUPPLYING PRODUCT AS DESCRIBED.

5 PROVIDE SUBMITTALS THAT INCLUDE THE LUMINAIRE, LAMP AND DIMMABLE LED DRIVER INFORMATION OF EACH LUMINAIRE, WITH APPLICABLE OPTIONS CLEARLY CHECKED OR HIGHLIGHTED. SUBMITTALS NOT INCLUDING THIS INFORMATION WILL BE RETURNED AS REJECTED BY THE ENGINEER OF RECORD.

6 PROVIDE FUNCTIONAL TESTING OF LIGHTING AND LIGHTING CONTROLS IN ACCORDANCE WITH THE 2021 OREGON ENERGY EFFICIENCY SPECIALY CODE (OEESC) FUNCTIONAL TESTING REQUIREMENTS

PANELBOARD: 1PGS (E)

	MAIN LUG ONLY BUS AMPACITY: 225 A EQUIPMENT RATING: 120/208		4 WIRF	_						ENCLO		SURFACE TYPE 1		Access	ories:	
	AIC RATING: SEE ON						SUPPLIED FROM:									
						d (VA)			1							
								LUa								
						Α	в	с	Α	в	с			Туре		
скт	Description/Location	Туре	C.B.	Pole	Note							Note Pole	C.B.	- 71	Description/Location	
1	EXISTING		20 A	1		0			0			1	20 A		EXISTING	
3	EXISTING		20 A	1			0			0		1	20 A		EXISTING	
5	EXISTING		20 A	1				0			0	1	20 A		EXISTING	
7	EXISTING		20 A	1		0			0			1	20 A		EXISTING	
9	EXISTING		20 A	1			0			0		1	20 A		EXISTING	
11	EXISTING		20 A	1				0			0	1	20 A		EXISTING	
13	EXISTING		20 A	1		0			0			1	20 A		EXISTING	
15	EXISTING		20 A	1			0			360		1	20 A	R	BATHROOM RECEPTACLES	
17	EXISTING		20 A	1				0			19	1	20 A	Motor	BATHROOM EXHAUST FANS	
19	EXISTING		20 A	1		0			0			1	20 A		EXISTING	
21	EXISTING		20 A	1			0			0		1	20 A		EXISTING	
23	EXISTING		20 A	1				0			0	1	20 A		EXISTING	
25	EXISTING		20 A	1		0			0			1	20 A		EXISTING	
27	EXISTING		20 A	1			0			0		1	20 A		EXISTING	
29	EXISTING		20 A	1				0			0	1	20 A		EXISTING	
31	EXISTING		20 A	1		0			0			1	20 A		EXISTING	
33	EXISTING		20 A	1			0			0		1	20 A		EXISTING	
35	EXISTING		20 A	1				0			0	1	20 A		EXISTING	
37	EXISTING		20 A	1		0			0			1	20 A		EXISTING	
39	EXISTING		20 A	1			0			0		1	20 A		EXISTING	
41	EXISTING		20 A	1				0			0	1	20 A		EXISTING	
	Total Connected load Ph. A					0 A		F	Panel Co	onnecte	d Load:	0.4 kVA			1.1 A	
	Total Connected load Ph. B Total Connected load Ph. C					3 A 0 A			Total	Deman	d Load:	0.4 kVA			1.1 A	
Notes:																

RE S	CHEDI	JLE			
UL/IP RATING	DRIVER/P OWER SUPPLY	LIGHT SOURCE	INPUT WATTS	MFG/CATALOG #	NOTES
. DAMP	INTEGRAL DRIVER; 0-10V DIMMING	NOMINAL 1000 LUMENS, 80+ CRI, MATCH COLOR TEMPERATURE TO EXISTING IN BUILDING	8.8	GOTHAM EVO4 SERIES OR SIMILAR	
DAMP	INTEGRAL DRIVER; 0-10V DIMMING	NOMINAL 500 LUMENS PER FOOT; 80CRI; MATCH COLOR TEMPERATURE TO EXISTING IN SPACE	10.6	AXIS AIR SERIES OR SIMILAR	
. DAMP	INTEGRAL DRIVER	LED; GREEN LETTERING	2.0	EVENLITE RAZOR SERIES; ISOLITE, PATHWAY, SURE-LITES TPX, BARRON LIGHTING, OR APPROVED	

CEF-01CEF-02EWH-1TEWH-2GENERAL MECA. THE ABO MECHANIB. MOCP = N MCA = MIC. PROVIDE SCHEDUIMECHANICAL E 11FAN TO BWIRE/CONDUIT 2022022			N
 A. THE ABO MECHANI B. MOCP = M MCA = MI C. PROVIDE SCHEDUI MECHANICAL E 1 FAN TO B WIRE/CONDUIT 202 2 #1 	CE CE E\ E\	EF-01 EF-02 WH-1 WH-2	
MECHANI B. MOCP = M MCA = MI C. PROVIDE SCHEDUL MECHANICAL E 1 FAN TO B WIRE/CONDUIT 202 2 #1	GEN		
MCA = MI C. PROVIDE SCHEDUI <u>MECHANICAL E</u> 1 FAN TO B <u>WIRE/CONDUIT</u> 202 2 #1	A.		
SCHEDUL <u>MECHANICAL E</u> 1 FAN TO B <u>WIRE/CONDUIT</u> 202 2 #1	В.		
1 FAN TO B <u>WIRE/CONDUIT</u> 202 2 #1	C.		
WIRE/CONDUIT 202 2 #1	MEC	HANICAL	. E
202 2 #1	1	FAN TC) B
202 2110	2	02 2	#1

N	IAIN CIRCUIT BREAKER 125 A BUS AMPACITY: 125 A									MOUI ENCLO	NTING: SURE:				Acces	sories
	EQUIPMENT RATING: 480/277	V, 3PH,	4 WIRE	Ξ						LOC	ATION:					
	AIC RATING: SEE ON	IE-LINE I	DIAGRA	٩М					SUF	PPLIED	FROM:					
								Loa	d (VA)]				1
скт	Description/Location	Туре	С.В.	Pole	Note	A	в	С	A	в	с	Note	Pole	С.В.	Туре	
1	EXISTING		20 A	1		0			0				3	20 A		
3	EXISTING		20 A	1			0			0						
5	EXISTING		20 A	1				0			0					
7	EWH-1	W	20 A	1		4,155			0				1	20 A		
9	EWH-2	W	50 A	1			9,972			0			1	20 A		
11	BUSSED SPACE			1									1			
13	EXISTING		20 A	3		0			0				1	20 A		
15							0			0			1	20 A		
17								0			0		1	20 A		
19	EXISTING		20 A	3		0							1			
21							0						1			
23								0					1			
25	BUSSED SPACE			1									1			
27	BUSSED SPACE			1									1			
29	BUSSED SPACE			1									1			
	Total Connected load Ph. A					17 A		F	Panel C	onnecte	d Load:	14.1 k	VA			17.0 A
	Total Connected load Ph. B Total Connected load Ph. C					38 A 0 A			Total	Deman	d Load:	17.7 k	VA			21.2 /

				LOAD		CIRCUIT	WIRE /	
DESCRIPTION	LOCATION	VOLTS	PH	(VA)	MOCP	NUMBER	CONDUIT	NOTES
EXHAUST FAN	ADA RR A101	120	1	9.4	20	1PGS-18	202	1
EXHAUST FAN	ADA RR A102	120	1	9.4	20	1PGS-18	202	1
ANKLESS WATER HEATER	LEVEL 1 RESTROOMS	277	1	4155.0	20	4LGS-7	202	
ANK LESS WATER HEATER	LEVEL 1 COUNTER	277	1	9972.0	50	4LGS-9	502	
AXIMUM OVER CURRENT PI IIMUM CIRCUIT AMPACITY DISCONNECTING MEANS FO		NT LISTED I	N THE S	CHEDULE	E ABOVE, E	XCEPT AS SPE	CIFICALLY NOTE	ED OTHERWISE IN
E NOTES, BELOW. QUIPMENT CONNECTION SC	HEDULE NOTES							

